

## UISP Console



## Mechanical

|                     |                                               |
|---------------------|-----------------------------------------------|
| Dimensions          | 210.4 x 140.2 x 43.7 mm (8.28 x 5.52 x 1.72") |
| Weight              | 1.45 kg (3.2 lb)                              |
| Enclosure materials | SGCC steel, polycarbonate                     |

## Hardware

|                         |                                                                                                                                 |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Networking interface    | (8) 10/100/1,000 MbE RJ45 LAN ports<br>(1) 10/100/1,000 MbE RJ45 WAN port<br>(1) 1/10G SFP+ LAN port<br>(1) 1/10G SFP+ WAN port |
| Management interface    | Ethernet In-Band<br>Bluetooth                                                                                                   |
| Processor               | Quad-core ARM® Cortex®-A57 at 1.7 GHz                                                                                           |
| Memory                  | 4 GB DDR4                                                                                                                       |
| Onboard flash storage   | 16 GB eMMC                                                                                                                      |
| Onboard storage         | 128 GB SSD                                                                                                                      |
| Card slot               | (1) microSD                                                                                                                     |
| Power method            | (1) External AC/DC adapter<br>(1) Power TransPort DC input 27V DC, 1.5A                                                         |
| Power supply            | 24V DC, 2.5A power adapter (included)                                                                                           |
| Supported voltage range | 24–28V DC                                                                                                                       |
| Max. power consumption  | 30W                                                                                                                             |
| ESD/EMP protection      | Air: ± 15kV, contact: ± 8kV                                                                                                     |
| Operating temperature   | -10 to 50° C (14 to 122° F)                                                                                                     |
| Operating humidity      | 5 to 95% non-condensing                                                                                                         |
| Certifications          | CE, FCC, IC                                                                                                                     |

## LEDs

|                 |                     |
|-----------------|---------------------|
| System          | Status              |
| RJ45 data ports | Speed/link/activity |
| SFP+ data ports | Speed/link/activity |

