

# ROLINE Cat.5e (Class D) Keystone Jack, RJ-45, UTP, light grey

|                    |               |
|--------------------|---------------|
| Product No.        | 26.11.0343    |
| Manufacturer       | ROLINE        |
| Manufacturer No.   | 26.11.0343    |
| EAN (single piece) | 7611990170548 |



## 19"-Patchpanel with Keystone Modules of ROLINE Quality!

- The system is composed of a 19" patch panel frame and the UTP Cat.5e RJ-45 keystone jack
  - Assembling takes place over LSA-plus
  - Colour code on the keystone jacks based on the standard EIA/TIA 568 A and 568 B
  - Colour: Light grey
  - For a structured unshielded Cat.5e cabling system we recommend to use the following components:  
ROLINE Cat.5e UTP Cable, Solid Wire, AWG24: 21.15.0512 (100 m), 21.15.0511 (300 m)  
ROLINE Flush Mount Wall Jack for Keystone, unloaded: 25.16.8579  
ROLINE Cat.5e Keystone, RJ-45, unshielded: 26.11.0343 (light grey), 26.11.0342 (black)  
ROLINE Cat.5e 19" Keystone Patch Panel, 24 Ports, unshielded: 26.11.0344 (black), 26.11.0345 (light grey)  
ROLINE Cat.5e UTP Patch Cord, grey, 5 m: 21.15.0505
- Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class D specification.

| Technical specifications |                          |
|--------------------------|--------------------------|
| Manufacturer             | ROLINE                   |
| Product group            | Connection technology TP |
| Product type             | RJ45 Keystone Jack       |
| Colour                   | grey                     |

|                           |                     |
|---------------------------|---------------------|
| Shield type               | Not screened        |
| Transfer quality          | Cat5e / Class D     |
| Cabinet system            | 19"-Technique       |
| Quantity of ports         | max. 24             |
| Assembly cable connection | Krone LSAplus       |
| Assignment                | EIA/TIA 568A & 568B |
| Modular assembly          | Yes                 |
| Connection direction      | Straight            |