



FCS-5096 Version: 1

GEMINI Zoom IP Network Camera, 2-Megapixel, H.265, 802.3at PoE, 4.3X Optical Zoom, IR LEDs, Indoor/Outdoor, Vandalproof

The LevelOne FCS-5096 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3at standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5096 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 60 fps High Frame Rate (HFR) video in 1080p
- Video compression: H.264, H.265
- Supports 4.3X optical zoom
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK10-rated housing
- Weatherproof IP67-rated housing
- Built-in infrared LEDs for night viewing up to 50m
- Built-in Micro SDHC/SDXC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Image Sensor:

1/2.8" Progressive Scan CMOS

Lens:

2.8 to 12 mm

Port:

1 x RJ-45 10/100 Mbps PoE port

Power Connector

1 x MicroSDHC/ MicroSDXC card slot

1 X 1Vp 1Vp-p composite output (75 Ω/BNC)

1 X Terminal Block DI/DO (max 12 VDC, 30 mA)

1 x Audio in/Out

1 X Terminal Block 12 VDC



Button/Knob:
Reset Button

Indicator:
Power

IR Cut Filter:
Removable infrared-cut filter for day & night function

IR LED:
IR LEDs for illumination up to 50m

Shutter Time:
1/3 s to 1/100,000 s

Angle of View:
Horizontal field of view: 105°to 35°
Vertical field of view: 56°to 20°
Diagonal field of view: 126°to 40.5°

Pan/Tilt/Zoom:
4.3X Optical Zoom

Video Compression:
H.265, H.264, MJPEG(sub stream)

Resolution:
50Hz: 50fps (1920 × 1080, 1280 × 960, 1280×720)
60Hz: 60fps (1920 × 1080, 1280 × 960, 1280×720)

Output Video Format:
AVI

Audio Compression:
G722.1/G711ulaw/G711alaw/G726/MP2L2/PCM

Power Input:
12 V DC ± DC ± 25%, PoE (802.at)

Power Consumption:
12 VDC, 1.3A, max. 15.5W
PoE (802.3at, 42.5V to 57V), 0.5A to 0.1A, max. 17.5W

Data Rate:
32 Kbps to 16 Mbps

Storage Capacity:
Built-in microSD/SDHC/SDXC slot, up to 128 GB

Features

General:

Motion Detection, Rotated Mode, Mirror, Color Adjustment (Brightness, Contrast, Saturation), Sharpness Adjustment, Anti-Flicker, Watermark, Privacy Mask, Automatic gain control (AGC) .

PoE:

PoE(802.3at)

Security:

One-key Reset, Heartbeat, Password Protection, IPv4, IPv6, File Management, Object Removal Detection, IP address filtering.

Management:

Event Triggers (Network Disconnected, IP address Conflict, Illegal Login, HDD Full, HDD Error, Alarm Input, Alarm Output, Line Crossing Detection, Intrusion Detection, Face detection)

Video:

120dB Wide Dynamic Range, BLC, Auto White Balance (AWB), Privacy Mask (up to 5 region), 3D DNR, Triple Stream

Audio:

8kHz/16kHz/32kHz/44.1kHz/48kHz

Performance**Number of Clients:**

32

Frame Rate (fps):**Main Stream**

50Hz: 50fps (1920 × 1080, 1280 × 960, 1280×720)

60Hz: 60fps (1920 × 1080, 1280 × 960, 1280×720)

Sub Stream

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream

50Hz: 25fps (1920 × 1080, 1280×720, 640 × 360, 352 × 288)

60Hz: 30fps (1920 × 1080, 1280×720, 640 × 360, 352 × 240)

Minimum illumination:

Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR

B/W: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR

Environment**Operating Temperature (°C):**

-30 °C to +60 °C (-22 °F to +140 °F)

Operating Humidity (Non-condensing):

Humidity 95%

Physical Specifications**Dimensions (W x D x H mm):**

144.13×332.73 mm (5.67"× 13.10")

Weight (g):

1893 g (4.17l b.)

Color:

White

Approval and Compliance**EMI/EMS:**

CE,FCC,UL

Safety:

IK10

Environmental Test:

IP67

Others:

Manufactured in ISO-9001 and ISO-14001 certified factory

Others



Supported Browsers:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Compatibility:

ONVIF

Order Information

FCS-5096

Package Contents

FCS-5096

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

Optional Accessory



CAS-7344

Pole Mount Bracket, Clamping Range 2.6"-5"



CAS-7345

Corner Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.