



## Lexmark MX632adwe

Exceptional performance, secure and sustainable



# Lexmark MX632adwe

With exceptional performance and secure design the Lexmark MX632adwe multi-function printer (copy/scan/print/fax) delivers enhanced productivity up to 47 ppm\* on A4 paper and a toner yield up to 31,000 pages\*\*. Engineered for long life with environmental certifications and advanced power management, this efficient model has a high sustainability. Fast time to first print, superior print quality and easy-to-use touch screen.

## Secure by design

Lexmark expertise helps customers protect their data, their device and their network. Our security ecosystem is designed to overcome the most complex data challenges. And now we've added the Trusted Platform Module (TPM)\*\*\*, which includes on-board authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint. TPM meets stringent industry and US government security standards including Common Criteria and Federal Information Processing Standard (FIPS).

## Proprietary technology

We own core technology across hardware, firmware, services, and solutions, creating seamless connections designed to reduce the risk of security gaps between your document, your device and your network. Our expertise is our customer's benefit.

## Sustainability

With certifications in Energy Star®, Blue Angel, RoHS, EPEAT® Silver. Models are sustainable for today and beyond. Lexmark is an industry leader of recycled content with products using at least 39% PCR content and continual focus on improvement. This line is also engineered for Long Life and designed to last and reduce waste.

## Intelligent Design

Every touch point is designed to withstand high usage while meeting accessibility standards. Steel frames support the device and provide durability to help ensure consistent long-

term performance. Products are designed for long service life with long-life components and are easily serviced with few tools.



## Optimised productivity

Increase productivity with optimised performance. Print at up to 47 pages per minute\* (A4) and capture information quickly with scan speeds of up to 49 images per minute (A4) for one-sided scanning, and up to 98 images per minute (A4) for two-sided scanning.

## Manageability

These IoT-ready devices can be remotely managed, including setup, configuration, consumables management, and diagnostics. Wireless capability gives freedom of access and remote firmware updates make it easy to upgrade to the latest apps and security features. Our mobile printing app makes it easier to monitor and manage your print jobs from remote locations, all from the touch of your phone.


This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous mono declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19752. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark MX632adwe



- 1 **Multifunction product with 17.8 cm touch screen**  
513.7 x 479 x 452.1 mm
- 2 **250-Sheet output bin**  
Dimensions included as part of base model
- 3 **100-Sheet multipurpose feeder**  
Dimensions included as part of base model
- 4 **550-Sheet tray**  
Dimensions included as part of base model
- 5 **250-Sheet Tray**  
78.1 x 389 x 373.7 mm
- 6 **550-Sheet Tray**  
108.2 x 389 x 373.7 mm

- 7 **550-Sheet Lockable Tray**  
108.2 x 389 x 373.7 mm
- 8 **Printer Stand (adjustable height)**  
584 x 597 x 597 mm
- 9 **Swivel cabinet (25 cm, incl. storage)**  
263 x 476 x 600 mm
- 10 **Convenience Stapler HV**  
82 x 109 x 121 mm



**P/N**  
38S0910

**Hardware**  
Lexmark MX632adwe

**P/N**  
35S8500  
66S0XAO  
66S0Z00  
66S0ZAO  
66S2000  
66S2X00

**Supplies**  
Staple Cartridges  
Lexmark MS631, 632, MX632 31K Toner Cartridge  
Lexmark MS531, 631, 632, 639, MX532, 632, M/XM3350 Return Programme 75K Imaging Unit  
Lexmark MS531, 631, 632, 639, MX532, 632 75K Imaging Unit  
Lexmark MS531, 631, 632, MX532, 632 Return Programme 5K Toner Cartridge  
Lexmark MS631, 632, MX632 Return Programme 31K Toner Cartridge

**P/N**  
38S2910  
38S3110  
38S3130  
47C4590

**Paper Handling**  
250-Sheet Tray  
550-Sheet Tray  
550-Sheet Lockable Tray  
Convenience Stapler

**P/N**  
27X0400  
57X9528

**Memory Options**  
500+ GB Hard Disk  
Intelligent Storage Drive (ISD)

**P/N**  
57X0225  
57X0235  
57X0300  
57X0301  
82S1203  
82S1204

**Application Solutions**  
Desktop Contactless Reader  
Contactless Front Solutions Module (Primary)  
Contact Authentication Device  
Contactless Authentication Device  
IPDS License  
Bar Code License

**P/N**  
1021231  
1021294  
27X0900  
27X0901  
27X0912  
57X7040  
SPD0002

**Connectivity**  
Parallel Cable (IEEE 1284 A-B, 3 meter)  
USB Cable (2 meter)  
MS610de, MX51x, MX611 RS-232C Serial Interface Card  
MS610de, MX51x, MX611 Parallel 1284-B Interface Card  
Lexmark MarkNet™ N8230 Fiber Ethernet Print Server  
English Keyboard Kit  
Surge protective device

**P/N**  
3073173  
35S8502

**Furniture**  
Swivel cabinet (25 cm, incl. storage)  
Printer Stand (adjustable height)

| Product Specifications                        |                                                                                                                                                                                   | Lexmark MX632adwe |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Printing                                      |                                                                                                                                                                                   |                   |
| Display                                       | Lexmark e-Task 7-inch (17.8 cm) colour touch screen                                                                                                                               |                   |
| Print speed                                   | up to: black: 47 ppm <sup>1</sup> (A4)                                                                                                                                            |                   |
| Time to first page                            | as fast as: black: 6 seconds                                                                                                                                                      |                   |
| Print resolution                              | black: 1200 x 1200 dpi, 1200 IQ (1200 x 600 dpi)                                                                                                                                  |                   |
| Memory                                        | standard: 2048 MB / maximum: 2048 MB                                                                                                                                              |                   |
| Hard Disk                                     | Intelligent Storage Drive available; Magnetic Hard Disk available                                                                                                                 |                   |
| Recommended monthly page volume               | 2,000 - 20,000 pages <sup>2</sup>                                                                                                                                                 |                   |
| Maximum monthly duty cycle                    | up to: 175,000 pages per month <sup>3</sup>                                                                                                                                       |                   |
| Copying                                       |                                                                                                                                                                                   |                   |
| Copy speed                                    | up to: black: 47 cpm <sup>1</sup> (A4)                                                                                                                                            |                   |
| Time to first copy                            | as fast as: black: 6.5 seconds                                                                                                                                                    |                   |
| Scanning                                      |                                                                                                                                                                                   |                   |
| ADF scan                                      | DADF (single pass Duplex)                                                                                                                                                         |                   |
| Duplex scan speed                             | up to: black: 98/104 spm (A4) / colour: 79.8/84 spm (A4)                                                                                                                          |                   |
| Simplex scan speed                            | up to: black: 49/52 spm (A4) / colour: 39.9/42 spm (A4)                                                                                                                           |                   |
| ADF paper input capacity                      | up to: 100 pages                                                                                                                                                                  |                   |
| Faxing                                        |                                                                                                                                                                                   |                   |
| Modem speed                                   | ITU T.30, V.34 Half-Duplex, 33.6 kbps                                                                                                                                             |                   |
| Supplies <sup>4</sup>                         |                                                                                                                                                                                   |                   |
| Cartridge yields                              | up to: 31,000 <sup>5</sup> -page Black Cartridge                                                                                                                                  |                   |
| Imaging unit yield                            | up to: 75,000 pages, based on average 3 pages per print job and 5% coverage                                                                                                       |                   |
| Cartridge(s) shipped with product             | 5000 <sup>5</sup> -page starter Return Programme toner cartridge <sup>5</sup>                                                                                                     |                   |
| Paper Handling                                |                                                                                                                                                                                   |                   |
| Standard paper handling                       | 100-Sheet Multipurpose Feeder, 250-Sheet Output Bin, Integrated Duplex, 550-Sheet Input                                                                                           |                   |
| Optional paper handling                       | 550-Sheet Lockable Tray, 250-Sheet Tray, 550-Sheet Tray                                                                                                                           |                   |
| Paper input capacity                          | up to: standard: 650 pages / maximum: 2300 pages                                                                                                                                  |                   |
| Paper output capacity                         | up to: standard: 250 pages / maximum: 250 pages                                                                                                                                   |                   |
| Media types supported                         | Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide                                                                                      |                   |
| Media sizes supported                         | A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope               |                   |
| General Information <sup>6</sup>              |                                                                                                                                                                                   |                   |
| Standard connectivity                         | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B) |                   |
| Optional network ports / Optional local ports | MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial                                                                       |                   |
| Noise Level                                   | Operating: 55 dBA (Print) / 57 dBA (Copy) / 52 dBA (Scan)                                                                                                                         |                   |
| Specified operating environment               | Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity                                                             |                   |
| Product guarantee                             | 1-Year Onsite Service, Next Business Day                                                                                                                                          |                   |
| Size / Weight                                 | HxWxD: 513.7 x 479 x 452.1 mm / 21.3 kg                                                                                                                                           |                   |
| Energy Star Typical Electricity Consumption   | TEC: 0.64 kWh per week                                                                                                                                                            |                   |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average standard page yield value declared in accordance with ISO/IEC 19752. <sup>6</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2023 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).