



FSP SFX PRO 450W power supply unit 24-pin ATX Black

Brand : FSP

Product code: PPA450AA00

Product name : SFX PRO 450W

- Compliance with the newest SFX12V V3.3
- Efficiency $\geq$ 85% at typical load
- Intelligent fan speed control
- 80Plus® bronze certified
- PS2 bracket for easy fitting into ATX case
- Black ribbon cables
- 80mm intelligent fan control
- Intel latest CPU ready

- Full protections OCP, OVP, SCP, OPP, OTP
450W, 80 PLUS Bronze, SFX12V, 80mm

FSP SFX PRO 450W. Total power: 450 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz.
Motherboard power connector: 24-pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: SFX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 8 cm. Width: 100 mm, Depth: 125 mm, Height: 63 mm



Power		Ports & interfaces	
Total power *	450 W	PCI Express power connectors (6+2 pin)	2
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	Floppy drive power connector	1
Maximum input current (@110V)	6 A	Floppy disk drive connector	✓
Maximum input current (@220V)	2.5 A	Cabling type	Non-Modular
Power Factor Correction (PFC) type	Active	Performance	
Combined power (+3.3V)	85 W	80 PLUS certification *	80 PLUS Bronze
Combined power (+12V)	450 W	Purpose *	PC
Combined power (+5V)	85 W	Power supply unit (PSU) form factor *	SFX
Combined power (-12V)	3.6 W	Noise level	43 dB
Combined power (+5Vsb)	12.5 W	Bearing technology	Rifle
Max output current (+3.3V)	16 A	Mean time between failures (MTBF)	100000 h
Max output current (+12V)	37.5 A	Design	
Max output current (+5V)	16 A	Product colour	Black
Max output current (-12V)	0.3 A	Cooling type	Active
Max output current (+5Vsb)	2.5 A	Fan diameter	8 cm
Efficiency	85%	Number of fans	1 fan(s)
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit	Fan location	Top
Ports & interfaces		On/off switch	✓
Motherboard power connector *	24-pin ATX	Weight & dimensions	
Number of SATA power connectors	3	Width	100 mm
Peripheral (Molex) power connectors (4-pin) *	3	Depth	125 mm
		Height	63 mm
		Weight	1.22 kg
Logistics data			
		Harmonized System (HS) code	84733020



4713224522123

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-MAY-2024. Prints or copies of Information are only valid on the printed Publication date