# Epson EB-L260F data projector Standard throw projector 4600 ANSI lumens 3LCD 1080p (1920x1080) White



**Brand :** Epson

**Product code:** V11HA69080

**Product name :** EB-L260F



- 4,600 lumens brightness display Full HD crisp images and bright colours, even in well-lit rooms
- A scalable display Flexibile scalable display from 31 inches up to 310 inches
- Stream content easily Wireless, MTR auto power-on by HDMI and easy smart stick connection
- Fit and forget reliability Easy installation with multi-projection and signage function
- The complete solution With an incredible contrast ratio of 2,500,000:1, the EB-L260F delivers vivid, lifelike content and defined shadow detail with deeper blacks

4600 - 3200 Lumen, 1080p, 16:9, 2500000:1, 10 Bits, 192 Hz - 240 Hz, 260W, AC 220-240 V, 50-60 Hz

| Projector | |
|---|---|
| Screen size compatibility * | 787.4 - 7874 mm (31 - 310") |
| Projection distance (wide) | 0.9 - 9.1 m |
| Projector brightness * | 4600 ANSI lumens |
| Projection technology * | 3LCD |
| Projector native resolution * | 1080p (1920x1080) |
| Contrast ratio (typical) * | 2500000:1 |
| Native aspect ratio * | 16:9 |
| Number of colours | 1.07 billion colours |
| Projector brightness (economic mode) | 3200 ANSI lumens |
| Vertical scan range | 192 - 240 Hz |
| Keystone correction, horizontal | 30° |
| Keystone correction, vertical | 30° |
| Heat dissipation | 884 BTU/h |

| Light source | |
|---|---|
| Light source type * | Laser |
| Service life of light source * | 20000 h |
| Service life of light source (economic mode) | 30000 h |

| Lens system | |
|---|---|
| Focus * | Manual |
| Focal length range | 18.2 - 29.1 mm |
| Aperture range (F-F) | 1.51 - 1.77 |
| Zoom capability | ✓ |
| Zoom type | Manual |
| Zoom ratio | 1:1.62 |
| Throw ratio | 1.32 - 2.12:1 |
| Offset | 1000% |

| Video | |
|---|---|
| Full HD * | ✓ |
| Video colour modes | Blackboard, DICOM simulation mode, Dynamic, Multi-projection, Presentation, sRGB |

| Ports & interfaces | |
|---|---|
| USB 2.0 ports quantity * | 2 |
| USB 2.0 Type-A ports quantity | 1 |
| Audio (L/R) in * | 2 |
| Audio (L/R) out | 1 |
| Microphone in | ✓ |
| Serial interface type * | RS-232C |
| VGA (D-Sub) ports quantity * | 3 |

| Network | |
|---|---|
| Wi-Fi * | ✓ |
| Wi-Fi standards | Wi-Fi 5 (802.11ac) |
| Miracast | ✓ |

| Features | |
|---|---|
| Noise level (economic mode) | 27 dB |
| HDCP | ✓ |
| Projection modes | Ceiling, Front |
| On Screen Display (OSD) | ✓ |
| Screen mirroring | ✓ |
| Noise level * | 37 dB |
| Air filter | ✓ |
| Password protection | ✓ |

| Multimedia | |
|---|---|
| Built-in speaker(s) * | ✓ |
| RMS rated power | 16 W |

| Design | |
|---|---|
| Product type * | Standard throw projector |
| Product colour * | White |
| Placement | Ceiling, Desktop, Floor, Wall |
| Cable lock slot | ✓ |
| Cable lock slot type | Kensington |

| Power | |
|---|---|
| Power source * | AC |
| Power consumption (typical) * | 199 W |
| Power consumption (standby) * | 0.5 W |
| Power consumption (max) | 260 W |
| Power consumption (economy mode) | 144 W |
| AC input voltage | 220 - 240 V |
| AC input frequency | 50 - 60 Hz |

| Operational conditions | |
|---|---|
| Storage temperature (T-T) | -10 - 60 °C |
| Operating relative humidity (H-H) | 20 - 80% |
| Storage relative humidity (H-H) | 10 - 90% |

| Weight & dimensions | |
|---|---|
| Width | 325 mm |
| Depth | 299 mm |
| Height | 90 mm |
| Weight * | 4.2 kg |

| Ports & interfaces | |
|---|---|
| HDMI ports quantity * | 2 |
| Composite video in * | 1 |
| AC (power) in | ✓ |
| Audio Return Channel (ARC) | ✓ |

| Network | |
|---|---|
| Ethernet LAN * | ✓ |
| Ethernet LAN (RJ-45) ports | 1 |

| Packaging content | |
|---|---|
| Remote control included * | ✓ |
| Batteries included | ✓ |
| Cables included | HDMI, Power |
| Bundled software | Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager, Epson Projector Management |

| Logistics data | |
|---|---|
| Quantity per pack | 1 pc(s) |



8715946715452

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-MAY-2024. Prints or copies of Information are only valid on the printed Publication date