



Canon PowerShot V10 Vlogging Kit 1" Compact camera 20 MP CMOS 5472 x 3648 pixels Silver

Brand : Canon

Product family: PowerShot

Product code: 5946C009

Product name : V10 Vlogging Kit

Canon PowerShot V10 Vlogging Kit. Camera type: Compact camera, Megapixel (approx.): 20 MP, Image sensor size: 1", Sensor type: CMOS, Maximum image resolution: 5472 x 3648 pixels. ISO sensitivity (max): 6400. Focal length range: 6.6 mm. Fastest camera shutter speed: 1/4000 s. Wi-Fi. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels. Display diagonal: 5.08 cm (2"), Touchscreen. Weight: 211 g. Product colour: Silver



Picture quality		Display	
Image sensor size *	1"	Display resolution	460000 dot
Camera type *	Compact camera	Display aspect ratio	3:2
Megapixel (approx.) *	20 MP	Flip-out screen	✓
Sensor type *	CMOS	Vari-angle LCD display	✓
Maximum image resolution *	5472 x 3648 pixels	Ports & interfaces	
Still image resolution(s) *	5472 x 3648, 3648 x 2432, 2736 x 1824, 2400 x 1600, 4864 x 3648, 3248 x 2432, 2432 x 1824, 2112 x 1600, 5472 x 3072, 3648 x 2048, 2736 x 1536, 2400 x 1344, 3648 x 3648, 2432 x 2432, 1824 x 1824, 1600 x 1600	USB version *	2.0
		USB connector	USB Type-C
		HDMI *	✓
		HDMI connector type	Micro
		Microphone in	✓
Supported aspect ratios	1:1, 3:2, 4:3, 16:9	Headphone connectivity	3.5 mm
Total megapixels	20.9 MP	Network	
Image formats supported *	JPEG	Bluetooth *	✓
Lens system		Bluetooth version	4.2
Focal length range	6.6 mm	Bluetooth Low Energy (BLE)	✓
Minimum focal length (35mm film equiv)	18 mm	Wi-Fi *	✓
Maximum focal length (35mm film equiv)	19 mm	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Maximum aperture number	2.8	Camera	
Lens structure (elements/groups)	8/7	White balance *	Auto, Cloudy, Daylight, Manual, Tungsten
Number of aspheric elements	3	White balance compensation (Blue/Amber)	±9
Focusing		White balance compensation (Magenta/Green)	±9
Focus *	TTL	Shooting modes *	Auto
Focus adjustment *	Auto/Manual	Self-timer delay *	2,10 s
Auto focusing (AF) modes *	Continuous Auto Focus	Dioptrre correction	✗
Auto Focus (AF) object detection	People	Languages support	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hebrew, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Ukrainian, Vietnamese
Face tracking	✓		
Closest focusing distance	0.05 m		
Auto Focus (AF) lock	✓		
Auto Focus (AF) assist beam	✗		
Exposure		Histogram	✓
ISO sensitivity (min) *	125	Live view	✓
ISO sensitivity (max) *	6400	Direct printing	✗
ISO sensitivity	125, 200, 400, 800, 6400		
Light exposure modes *	Auto, Manual		

Exposure		Camera	
Light exposure control	Program AE	GPS (satellite)	✗
Light exposure correction *	± 3EV (1/3EV step)	Orientation sensor	✓
Light metering *	Evaluative (Multi-pattern)	Anti-dust function	✗
Number of measurement zones	384	Smartphone/tablet remote support	✓
Shutter		View on smartphone	✓
Fastest camera shutter speed *	1/4000 s	Tripod mounting supported *	✓
Slowest camera shutter speed *	1 s	Image processor	DIGIC X
Camera shutter type	Electronic	Compatible products	Kamera Cage, Stereo-Richtmikrofon DM-E1, Kabellose Fernbedienung BR-E1, Schnittstellenkabel IFC-100 U 2.0, IFC-400U, USB-Netzadapter PD-E1, Griffstativ HG-100TBR, Stereo-Mikrofon DM-E100
Flash			
Flash exposure lock	✗		
External flash connector	✗		
Flash exposure compensation	✗		
Shoe mounting point	✗	Design	
Video		Product colour *	Silver
Video recording *	✓	Dustproof	✗
Maximum video resolution *	3840 x 2160 pixels	Splash proof	✗
HD type *	4K Ultra HD	Battery	
Video resolutions	3840 x 2160,1920 x 1080 pixels	Battery technology *	Lithium-Ion (Li-Ion)
Video recording time	55 min	Battery life (CIPA standard)	290 shots
Video formats supported	H.264	Number of batteries supported	1
Video recording ISO sensitivity (auto)	125-6400, 125-3200	Battery level indicator	✓
Video recording ISO sensitivity (manual)	125-6400, 125-3200	Compatible power supply / battery chargers	USB-Laden und Betreiben über PD-E1 Netzadapter
Colour sampling	YCbCr4:2:0 8-bit	Operational conditions	
Audio		Operating temperature (T-T)	0 - 40 °C
		Weight & dimensions	
Built-in microphone *	✓	Width	90 mm
Built-in speaker(s)	✓	Depth	34.3 mm
Audio system	stereo	Height	63.4 mm
Wind filter	✓	Weight	211 g
Audio formats supported	AAC, LPCM	Weight (including battery)	211 g
Memory		Packaging data	
Compatible memory cards *	MicroSD (TransFlash), MicroSDHC, MicroSDXC	Quantity per pack	1 pc(s)
Memory slots	1	Package width	158 mm
Display		Package depth	290 mm
Display *	LCD	Package height	118 mm
Touchscreen *	✓	Package weight	667 g
Display diagonal *	5.08 cm (2")	Packaging content	
		Hand strap	✓
		Neck strap included	✗
		Battery charger included	✗
		Batteries included	✓
		Lens cap included	✓
		Logistics data	
		Products per pallet	144 pc(s)



8714574676951

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-MAY-2024. Prints or copies of Information are only valid on the printed Publication date