



Model: PD-2120

Art.: 88882226

Small 20W PD-Charger, supporting PD-Charging with 5V, 9V and 12V as well as Quick-Charge 3.0.

With USB Type C and USB Type A port.

Input	Voltage	AC 100 - 240 V ~
	Current	max 0.6A
	Frequency	50/60Hz
Output	Power	max. 20W
	Current	max. 3,0A
	Voltage USB A	5V= (max. 3,0A) 9V= (max. 2,0A) 12V= (max. 1,5A)
	Voltage USB C	5V= (max. 3,0A) 9V= (max. 2,22A) 12V= (max. 1,67A)
	Connector	USB Type C USB Type A
Safety	Short Circuit Protection	+
	Over Power Protection	+
Economic data	Efficiency	88,00%
	Standby	< 0,1W
Environmental	Temperature	0°C - 40°C (im Betrieb) -20°C - 85°C (Lagerung)
	Humidity	5% - 90% (im Betrieb, nicht kondensierend) 0% - 95% (Lagerung, nicht kondensierend)
Scope of delivery		PD Charger, Manual
Warranty		12 Months
Logistic data	Dimension	80 x 42 x 22 mm
	Net weight	50 g
	Gross weight	60 g
	Article number	88882226
	GTIN	4260455648233
	Packing unit	1 pcs