

FIBER OPTIC CONNECTOR FC/UPC | SINGLEMODE | 0.9MM

Product code: 54171

Fiber optic connector for connecting optical fibers.
Connectors: FC/UPC
Fiber type: Singlemode

TECHNICAL DATA

TYPE CONNECTORS	FC/UPC
FIBER TYPE	Singlemode
USAGE	Indoor cable. Drop cable.
DIAMETER CABLE	0.9 mm
OPTICAL FIBER DIAMETER	125 m (657A, 657A2)
TIGHT BUFFER DIAMETER	250 m
WORKING TIME	About 100s (no fiber cut)
INSERTION LOSS	0.3 dB (1310nm, 1550nm)
FASTENING STRENGHT OF NAKED FIBER	> 5 N
FASTENING STRENGHT OF NAKED FIBER HOLDER	> 10 N
TENSILE STRENGTH	> 50 N
OPERATING TEMPERATURE	-40 C ~ +75 C
ON-LINE TENSILE STRENGTH (20N)	IL 0.5 dB RL 5 dB IL - insertion loss RL - return loss
MECHANICAL DURABILITY (500 TIMES)	IL 0.5 dB RL 5 dB
DROP-OFF TEST	IL 0.5 dB RL 5 dB
PACKAGE	Polybag

EAN CODE	5901878541716