

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
A	Art.-Nr. / Item No.	Beschreibung / Description		Länge / Length (L)	Kontaktwiderstand / Contact resistance	Max. Übertragungsrate / Max. data transmission rate	AD Kabelmantel / OD cable jacket	Kabeldurchmesser / Cable diameter			Pin-Belegung / Pin Assignment				A
B	61299	HDMI 2.0 Kabel Ferrite 0100 1,0m (15+1) sw		1000 ± 20 mm	5 Ω max.	18 Gbit/s	5.5 ± 0.2 mm	30AWG (1/0.254CCS) * 1P + AL) * 4P + (1/0.254CCS) * 1P + E + AM) * 1P + 30# (1/0.254CCS) * 4C + D (1/.0254CCS) + AL			CN1		CN2		B
	61300	HDMI 2.0 Kabel Ferrite 0150 1,5m (15+1) sw		1500 ± 30 mm	5 Ω max.	18 Gbit/s	5.5 ± 0.2 mm				1 3		1 3		
	61301	HDMI 2.0 Kabel Ferrite 0200 2,0m (15+1) sw		2000 ± 30 mm	5 Ω max.	18 Gbit/s	5.5 ± 0.2 mm				4 6		4 6		
	61302	HDMI 2.0 Kabel Ferrite 0300 3,0m (15+1) sw		3000 ± 50 mm	10 Ω max.	18 Gbit/s	5.5 ± 0.2 mm				7 9		7 9		
	61303	HDMI 2.0 Kabel Ferrite 0500 5,0m (15+1) sw		5000 ± 100 mm	10 Ω max.	10.2 Gbit/s	5.5 ± 0.2 mm	10 12		10 12		14 19		C	
61304	HDMI 2.0 Kabel Ferrite 1000 10,0m (15+1) sw		10000 ± 200 mm	20 Ω max.	10.2 Gbit/s	5.5 ± 0.2 mm	18 16		18 16		17 13				
C	61305	HDMI 2.0 Kabel Ferrite 1500 15,0m (15+1) sw		15000 ± 300 mm	30 Ω max.	10.2 Gbit/s	7 ± 0.2 mm	26AWG (1/0.40CCS) * 1P+AM) * 4P + (1/0.40CCS) * 1P + E + AM) * 1P + 30# (1/0.254CCS) + 4C + D (1.0/0.254CCS) + AL			2 18		15 16		D
D	Aderquerschnitt / Wire cross section													E	
E															F
F	High-Speed-HDMI™-Kabel mit Ethernet (Ferrite) - hochauflösende Signalübertragung mit bis zu 4K @ 60 Hz (Ultra HD 2160p) - vergoldete HDMI™-Steckverbinder - integrierter Ethernet-Kanal High Speed HDMI™ Cable with Ethernet (Ferrite) - high-definition signal transmission with up to 4K @ 60 Hz (Ultra HD 2160p) - gold-plated HDMI™ connectors - integrated Ethernet channel Anschlüsse: Material Kabelmantel: Isolationswiderstand: Ferritkern: Unterstützte Audiostandards: Weitere unterstützte Standards: 2x HDMI™-Stecker (Typ A) PVC 300 V ===, 10 MΩ min. 2x Enhanced Audio Return Channel (eARC), Audio Return Channel (ARC) HDR (High Dynamic Range), HDCP 2.2, HDMI™ Ethernet Channel (HEC), 3D, Consumer Electronics Control (CEC) Connections: Material cable jacket: Insulation resistance: Ferrite core: Supported audio standards: Other supported standards: 2x HDMI™ plug (Type A) PVC 300 V ===, 10 MΩ min. 2x Enhanced Audio Return Channel (eARC), Audio Return Channel (ARC) HDR (High Dynamic Range), HDCP 2.2, HDMI™ Ethernet Channel (HEC), 3D, Consumer Electronics Control (CEC) Änderungen Datum Name gez.: gepr.: Norm: Datum Name rs aw Änderungen vorbehalten / Subject to change Bezeichnung HDMI 2.0 Kabel Ferrite XXXX Xm (15+1) sw Zeichnungs-Nr.: Blatt 1/1 von 1 2 3 4 5 6 7 8 9 10 11 12 13 14														