

	1	2	3	4	5	6	7	8	9	10	11	12	13	14
A	Art.-Nr. / Item No.		Beschreibung / Description		Länge / Length (L)		Kontaktwiderstand / Contact resistance		Max. Übertragungsrate / Max. data transmission rate		AD Kabelmantel / OD cable jacket		Kabeldurchmesser / Cable diameter	
B	61299		HDMI 2.0 Kabel Ferrite 0100 1,0m (15+1) sw		1000 ± 20 mm		5 Ω max.		18 Gbit/s		5.5 ± 0.2 mm		30AWG (1/0.254CCS) * 1P + AL) * 4P + (1/0.254CCS) * 1P + E + AM) * 1P + 30# (1/0.254CCS) * 4C + D (1/.0254CCS) + AL	
	61300		HDMI 2.0 Kabel Ferrite 0150 1,5m (15+1) sw		1500 ± 30 mm		5 Ω max.		18 Gbit/s		5.5 ± 0.2 mm			
	61301		HDMI 2.0 Kabel Ferrite 0200 2,0m (15+1) sw		2000 ± 30 mm		5 Ω max.		18 Gbit/s		5.5 ± 0.2 mm			
	61302		HDMI 2.0 Kabel Ferrite 0300 3,0m (15+1) sw		3000 ± 50 mm		10 Ω max.		18 Gbit/s		5.5 ± 0.2 mm			
	61303		HDMI 2.0 Kabel Ferrite 0500 5,0m (15+1) sw		5000 ± 100 mm		10 Ω max.		10.2 Gbit/s		5.5 ± 0.2 mm			
	61304		HDMI 2.0 Kabel Ferrite 1000 10,0m (15+1) sw		10000 ± 200 mm		20 Ω max.		10.2 Gbit/s		5.5 ± 0.2 mm			
	61305		HDMI 2.0 Kabel Ferrite 1500 15,0m (15+1) sw		15000 ± 300 mm		30 Ω max.		10.2 Gbit/s		7 ± 0.2 mm		26AWG (1/0.40CCS) * 1P+AM) * 4P + (1/0.40CCS) * 1P + E + AM) * 1P + 30# (1/0.254CCS) + 4C + D (1.0/0.254CCS) + AL	
C														
D														
E														
F	High-Speed-HDMI™-Kabel mit Ethernet (Ferrite) - hochauflösende Signalübertragung mit bis zu 4K @ 60 Hz (Ultra HD 2160p) - vergoldete HDMI™-Steckverbinder - integrierter Ethernet-Kanal Anschlüsse: Material Kabelmantel: Isolationswiderstand: Ferritkern: Unterstützte Audiostandards: 2x HDMI™-Stecker (Typ A) PVC 300 V ===, 10 MΩ min. 2x Enhanced Audio Return Channel (eARC), Audio Return Channel (ARC) Weitere unterstützte Standards: HDR (High Dynamic Range), HDCP 2.2, HDMI™ Ethernet Channel (HEC), 3D, Consumer Electronics Control (CEC) High Speed HDMI™ Cable with Ethernet (Ferrite) - high-definition signal transmission with up to 4K @ 60 Hz (Ultra HD 2160p) - gold-plated HDMI™ connectors - integrated Ethernet channel Connections: Material cable jacket: Insulation resistance: Ferrite core: Supported audio standards: 2x HDMI™ plug (Type A) PVC 300 V ===, 10 MΩ min. 2x Enhanced Audio Return Channel (eARC), Audio Return Channel (ARC) Other supported standards: HDR (High Dynamic Range), HDCP 2.2, HDMI™ Ethernet Channel (HEC), 3D, Consumer Electronics Control (CEC)													
G														
H														
I	Änderungen Datum Name gez.: 09.02.2023 rs gepr.: 09.02.2023 aw Norm: Änderungen vorbehalten / Subject to change Bezeichnung HDMI 2.0 Kabel Ferrite XXXX Xm (15+1) sw Zeichnungs-Nr.: Blatt 1/1 von													
J	1	2	3	4	5	6	7	8	9	10	11	12	13	14