

bluechip SERVERline T40322s

Brand : bluechip

Product code: 850523

Product name : SERVERline T40322s

bluechip SERVERline T40322s. Processor family: Intel Xeon Silver, Processor frequency: 2 GHz, Processor model: 4410Y. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM, Memory layout (slots x size): 2 x 16 GB. Total storage capacity: 1.92 TB. Ethernet LAN. Optical drive type: DVD±RW. Power supply: 500 W. Chassis type: Tower



Processor		Graphics	
Processor manufacturer *	Intel	On-board graphics card model	Aspeed AST2600
Processor family *	Intel Xeon Silver	Network	
Processor generation	Intel Xeon Scalable 4th Gen	LAN controller	Intel® X550
Processor model *	4410Y	Ethernet LAN	✓
Processor frequency *	2 GHz	Ethernet interface type	10 Gigabit Ethernet
Processor boost frequency	3.9 GHz	Ports & interfaces	
Processor cores	12	Ethernet LAN (RJ-45) ports *	2
Processor cache	30 MB	USB 2.0 ports quantity	2
Motherboard chipset	Intel C741	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
Configurable TDP-down	4.5 W	VGA (D-Sub) ports quantity	1
Processor socket	LGA 4677 (Socket E)	Serial ports quantity	1
Bus type	OPI	Expansion slots	
Intelligent Platform Management Interface (IPMI) support	✓	PCI Express x8 slots	1
Memory		PCI Express x16 slots	2
Internal memory *	32 GB	Design	
Internal memory type *	DDR5-SDRAM	Chassis type *	Tower
Memory slots	8x DIMM	Product colour	Black
ECC	✓	Software	
Memory clock speed	4800 MHz	Operating system installed *	✗
Memory layout (slots x size)	2 x 16 GB	Processor special features	
Maximum internal memory *	2 TB	CPU configuration (max)	1
Storage		Intel Smart Response Technology version	1.00
Total storage capacity *	1.92 TB	Intel Stable Image Platform Program (SIPP) version	0.00
Number of SSDs installed	2	Intel Secure Key Technology version	1.00
SSD capacity	960 GB	Intel TSX-NI version	0.00
SSD interface	SATA III	Power	
SSD size	2.5"	Redundant power supply (RPS) support *	✗
Supported SSD sizes	2.5", 3.5"	Power supply *	500 W
RAID support *	✓	Weight & dimensions	
RAID levels	0, 1, 5, 10	Width	170 mm
Supported RAID controllers	Intel RSTe		
Hot-swap	✓		
Optical drive type *	DVD±RW		
Internal drive bays	8		
Supported storage drive interfaces	SAS, Serial ATA		

Graphics		Weight & dimensions	
On-board graphics card	✓	Depth	513 mm
		Height	340 mm
Other features			
Motherboard manufacturer		Supermicro X13SEM-TF	



4250749706985

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-MAY-2024. Prints or copies of Information are only valid on the printed Publication date