

HyperDrive^{Next}

HD4006GL


11 Port USB-C Hub

Dimensions:

Length x Width x Height (cm) - 12.6 x 4.9 x 1.5 cm

Weight (kg) - Approx. 0.098 Kg

SRP: £119.99 | €129.99



Product Specification – HD4006GL

Connection to host device

Connector type	USB-C*
Connector technology	USB 3.2 Gen 2 (10 Gbps)
Graphics Technology	DP Alt Mode

Host device port compatibility

USB 3	•
USB4	•
Thunderbolt 3	•
Thunderbolt 4	•

Video ports

HDMI	2x HDMI 2.0
Display Port	--
VGA	--
Video via High-speed USB / Thunderbolt port	--
Maximum no. of monitor(s)	2
Maximum resolution (single monitor)	4K @ 60 Hz**
Maximum resolution (multi-monitor)	2 x 4K @ 60 Hz**
HDR via HDMI	--

Connection Ports

USB-A (Power / Max data speed)	1x USB 3.2 Gen2 (10 Gbps) 1x USB 3.2 Gen1 (5 Gbps)
USB-C (Power / Max data speed)	2x USB 3.2 Gen2 (10 Gbps) 1x USB PD 3.1 (Max. 140 W)
Thunderbolt 3	--
Thunderbolt 4	--
RJ45 Ethernet	Gigabit Ethernet
3.5 mm Audio	•
Other audio ports	--
Memory cards	SD / microSD 4.0 (312 MB/s) - UHS-II card compatible*****

Power

USB Power Delivery to host device	- when hub is connected to optional USB-C PD 3.1 charger
Max. PD power / PD pass through to host	140 W PD 3.1 / up to 125 W pass through to host device***

Recommended USB-C chargers

Hyper HJG100 100 W GaN charger	•*****
Hyper HJG140 140 W Universal GaN charger	•
Targus APA108 100 W laptop charger	•*****

Host device system OS compatibility

Works with Windows®	•
Works with MacOS®	•
Works with ChromeOS®	•
Works with iOS®	•****
Works with Android®	•
Works with Samsung DEX	•**
Works With Linux Ubuntu™	--

Device compatibility

Windows® Laptop	•**
Microsoft Surface® Laptop	•**
ChromeBook®	•**
Apple iMac®	•*****
Apple MacBook Pro® / Air® 2016 - 2019	•*****
Apple MacBook Pro® / Air® M1 / M2 2020 - 2022	•*****
Apple MacBook Pro® / M1 / M2 Pro / Max 2021 - 2023	•*****
Apple iPad Pro® 2018 or later	•****
Apple iPad Air® 2020 or later	•****
Android® Tablet	•**
Android® Smartphone	•**

Other features

Construction material	Yes - with 100% recycled Aluminium and up to 85% PCR plastics where applicable
USB-C cable to host device	Built in cable to host device
Warranty	2 years

Content

What's in the box	• HD4006GL HyperDrive NEXT 11 port USB-C Hub • User Guide
-------------------	--

Notes

*Full hub data, video and power functionality will require host device with USB-C port compatible with DP Alt Mode, Power Delivery PD 3.1 and USB 3.2 Gen 1/ Gen 2.
**4K 60 Hz video required host device USB-C port compatible with DP1.4. Using extended desktop mode to dual monitors requires host device to be MST (Multi-Stream Transport) compatible.
*** when using optional 140 W USB-C PD 3.1 charger
**** Compatible with iPad® with USB-C/Thunderbolt™ port. Extended mode to single external monitor only and requires iPadOS 16 or later.
***** Maximum SD / microSD 4.0 transfer speed requires UHS-II compliant SD / microSD cards. Actual transfer speed depends SD / microSD card read and write speed specifications and host device processor and port capability.
***** up to 85 W pass through to host device when using 100 W USB-C PD charger
***** MacBook® does not comply with MST graphic protocol, extended mode compatibility limited to single monitor only