MPN: 0070-24143

43" 24/7 4K UHD surveillance monitor. Industrial-grade LED screen. Metal chassis design

PRODUCT CHARACTERISTICS



· 4K HD solution
· Industrial-grade LED screen
· Designed for CCTV
· High brightness, high contrast, high definition
· Adapts to the latest 3D digital filtering and 3D digital noise reduction technology
· Picture fast response
· 178° wide viewing angle
· High fidelity digital processing, brilliant and vivid video
· 24/7 working status, working continuously for 5 years
· Metal chassis design, anti-static, anti-magnetic field, anti-interference, no radiation
VESA size: 200x200

- 4K HD Solution
- 7/24 working Status Security monitor
- High brightness, High contrast, High definition
- Adapt newest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response
- 178 ° wide viewing angle
- Metal chassis design, Anti-static, Anti-magnetic field, Anti-interference, no radiation
- Humanize Menu
- Convenient Controller
- HDMI cable included
- 5 Year Warranty

Specifications

Design	**Detachable stand**	Yes
	Front bezel colour	Black
	Market positioning	Industrial
	Product colour	Black
Display	**3D**	Yes
	Aspect ratio	16:9
	Backlight type	LED
	Contrast ratio (typical)	1200:1
	Display brightness	350 cd/m²
	Display brightness (typical)	350 cd/m²
	Display diagonal	43 "
	Display resolution	3840 x 2160 pixels
	Display technology	LCD, LED

Display	**HD type**	4K Ultra HD
	Native aspect ratio	16:9
	Pixel pitch	0.2451(H)×0.2451(V) mm
	Response time	5 ms
	Viewable size, horizontal	94.1 cm
	Viewable size, vertical	52.9 cm
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	**On Screen Display (OSD) languages**	English
	Panel mounting interface	200 x 200 mm
	VESA mounting	Yes
Legal Information	**ADR Information**	No restrictions
	Country of Origin	China
	Tariff No.	8528529100
	UNSPSC Code	43211902
Operational conditions	**Operating temperature (T-T)**	-30 - +85 °C
Other features	**Accessories included**	Industrial PSU,Screw, Cable holder, Quick start guide
	Active display area (W x H)	941.184mm(W)×529.146mm(H) mm
	Analog signal format system	PAL, NTSC, SECAM
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 200 x 200
	Contrast ratio	1200:1
	Dimensions (WxDxH)	972 x 88 x 576 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	VESA mount 200 x 200 mm
	Noise filter	Yes
	Number of colours	1.073 billion colours
	Package dimensions (WxDxH)	1085 x 232 x 680 mm
	Picture enhancement	DNIe digital image processing
	Power consumption	100 W
	Speakers	2x3W
	Weight	19800 g
Package dimensions	**Depth (package,cm)**	23.2 cm
	Gross Weight (Package, kg)	24 kg
	Height (package,cm)	68 cm
	Width (package,cm)	108.5 cm
Packaging content	**Power adapter included**	Yes
	Quick start guide	Yes

Packaging content	**Screws included**	Yes
	Stand included	Yes
Performance	**Operating hours (hours/days)**	24/7
Ports & interfaces	**DisplayPorts quantity**	1
	HDMI ports quantity	3
	HDMI version	2.0
Power	**AC input frequency**	50/60 Hz
	AC input voltage	100-240 V
	Power consumption (average)	100 W
	Power supply type	Industrial
	Socket connector type	C13
Product dimensions	**Net Weight (Product, kg)**	19.8 kg
	Product Depth	8.8 cm
	Product Height	57.6 cm
	Product Width	97.2 cm
Vendor information	**Brand Name**	Ernitec
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
8	0070-24108-M
10.1	0070-24110-M-L
19	0070-24119-M
22	0070-24222-AC-M
32	0070-24232-M
43	0070-24143
49	0070-24149
55	0070-24155
65	0070-24165
75	0070-24175
86	0070-24186
98	0070-24198

Other images





