MPN: 0070-24149

49" 24/7 4K UHD surveillance monitor. Industrial-grade LED screen. Metal chassis design



Ernitec 49" Monitor: Exceptional 4K UHD Performance

Introducing the Ernitec 49" Monitor, a powerful display solution tailored for CCTV applications. With its 4K UHD resolution, this industrial-grade LED screen delivers outstanding image quality, ensuring high brightness, contrast, and clarity.

Key Features:

Stunning Visuals: Experience high definition with advanced 3D digital filtering and noise reduction technology for crystal-clear images.

Rapid Response: Enjoy fast picture response times and a 178° wide viewing angle, providing consistent quality from any position.

Reliable Operation: Built for 24/7 use, this monitor is designed to operate continuously for up to 5 years, making it a dependable choice for security monitoring.

Durable Design: The robust metal chassis is anti-static, anti-magnetic, and resistant to interference, ensuring safe operation without radiation.

User-Friendly Interface: Navigate effortlessly with a convenient controller and intuitive menu system.

Flexible Mounting: Compatible with VESA 400x200, allowing for easy installation in various environments.

The Ernitec 49" Monitor is your ideal partner for high-performance surveillance, combining durability with exceptional visual quality.

Upgrade your security setup today!

- 4K HD Solution
- 7/24 working Status Security monitor
- High brightness, High contrast, High definition
- Adapt newest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response
- 178 ° wide viewing angle
- Metal chassis design, Anti-static, Anti-magnetic field, Anti-interference, no radiation
- Humanize Menu
- Convenient Controller
- HDMI cable included
- 5 Year Warranty

Specifications

Design	**Detachable stand**	Yes

Design	**Front bezel colour**	Black
	Market positioning	Enterprise
	Product colour	Black
Display	**3D**	Yes
	Aspect ratio	16:9
	Backlight type	LED
	Contrast ratio (typical)	5000:1
	Display brightness	500 cd/m²
	Display brightness (typical)	350 cd/m²
	Display diagonal	49 "
	Display resolution	3840 x 2160 pixels
	Display technology	LCD, LED
	HD type	4K Ultra HD
	Native aspect ratio	16:9
	Pixel pitch	0.315(H)×0.315(V) mm
	Response time	5 ms
	Viewable size, horizontal	107.6 cm
	Viewable size, vertical	60.6 cm
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	**On Screen Display (OSD) languages**	English
	Panel mounting interface	400 x 200 mm
	VESA mounting	Yes
Legal Information	**ADR Information**	No restrictions
	Country of Origin	China
	Tariff No.	8528529100
	UNSPSC Code	43211902
Operational conditions	**Operating temperature (T-T)**	-30 - +85 °C
Other features	**Accessories included**	Industrial PSU,Screw, Cable holder, Quick start guide
	Active display area (W x H)	1095.84mm(W)×616.41mm(H) mm
	Analog signal format system	PAL, NTSC, SECAM
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 400 x 200
	Contrast ratio	4000:1
	Dimensions (WxDxH)	1103 x 76 x 649 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	VESA mount 400 x 200 mm
	Noise filter	Yes

Other features	**Number of colours**	1.073 billion colours
	Package dimensions (WxDxH)	1247 x 232 x 765 mm
	Picture enhancement	DNIe digital image processing
	Power consumption	110 W
	Speakers	2x3W (Stereo)
	Weight	24300 g
Package dimensions	**Depth (package,cm)**	23.2 cm
	Gross Weight (Package, kg)	29 kg
	Height (package,cm)	76.5 cm
	Width (package,cm)	124.7 cm
Packaging content	**Power adapter included**	Yes
	Quick start guide	Yes
	Screws included	Yes
	Stand included	Yes
Performance	**Operating hours (hours/days)**	24/7
Ports & interfaces	**AC (power) in**	Yes
	DisplayPorts quantity	1
	HDMI ports quantity	3
	HDMI version	2.0
Power	**AC input frequency**	50/60 Hz
	AC input voltage	100-240 V
	Power consumption (average)	120 W
	Power supply type	Industrial
	Socket connector type	C13
Product dimensions	**Net Weight (Product, kg)**	24.3 kg
	Product Depth	7.6 cm
	Product Height	64.9 cm
	Product Width	110.3 cm
Vendor information	**Brand Name**	Ernitec
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
8	0070-24108-M
10.1	0070-24110-M-L
19	0070-24119-M
22	0070-24222-AC-M
32	0070-24232-M
43	0070-24143
49	0070-24149
55	0070-24155
65	0070-24165
75	0070-24175
86	0070-24186
98	0070-24198

Other images





