



POLY Edge E220 IP Phone and PoE-enabled

Brand : POLY

Product code: 82M87AA

Product name : Edge E220 IP Phone and PoE-enabled

- The Poly Edge E220 IP desk phone is always-on, easy to use, secure, reliable, and stable. With everyday features at your fingertips, they're everything you want in an entry level or common area phone.
 - Rest assured that your devices, enhanced with Microban® antimicrobial product protection, stay cleaner, fresher, and more durable for longer. Protection that lasts the life of the product, actively reducing the growth of bacteria 24/7 ^[1].
 - Our most versatile phones today, the Poly E220 offer quality audio with Poly HD voice. They reduce noise and distractions with Poly NoiseBlockAI and Acoustic Fence technologies.
- Edge E220 IP Phone and PoE-enabled

POLY Edge E220 IP Phone and PoE-enabled:

A phone with high standards

Easy to use and packed with features, the Poly Edge E220 IP desk phone keeps you sounding professional and productive. Bring style to any desktop or reception area with cutting-edge design and stay on track with Poly noise reduction technology.



Design		Ports & interfaces	
Product type *	IP Phone	USB Type-C ports quantity	1
Handset type	Wired handset	Ethernet LAN (RJ-45) ports	2
Product colour *	Black	RJ-9 ports quantity	1
Wall mountable	✓	Certificates	
Phone features		Sustainability certificates	ENERGY STAR
Lines quantity *	4 lines	Power	
Caller ID *	✓	Power over Ethernet (PoE) *	✓
Display		Power consumption (Power over Ethernet (PoE))	13 W
Display	IPS	Operational conditions	
Display diagonal	7.11 cm (2.8")	Operating temperature (T-T)	0 - 40 °C
Display resolution	320 x 240 pixels	Operating relative humidity (H-H)	5 - 95%
Aspect ratio	9:16	Storage temperature (T-T)	-40 - 70 °C
Touchscreen *	✗	Weight & dimensions	
Audio		Package width	223 mm
Speakerphone *	✓	Package depth	255 mm
Voice codecs	G.711alaw, G.711ulaw, G.722, G.722.1, G.729ab, OPUS, iLBC	Package height	83 mm
Network		Package weight	880 g
Ethernet LAN *	✓	Packaging content	
Ethernet LAN interface type	Gigabit Ethernet	Mounting kit	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Handset	✓
Wi-Fi *	✗	Number of handles included *	1 pc(s)
Bluetooth *	✓	Cables included	LAN (RJ-45)
Bluetooth version	5.0		
Near Field Communication (NFC)	✓		

Logistics data

Country of origin	China
-------------------	-------



0197497341355



197497341355

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-MAY-2024. Prints or copies of Information are only valid on the printed Publication date