

## UTA-05

GaN III Universal Travel Adapter with  
2x USB-C PD 65W & QC 4+ / 2x USB-A



GaN III charging technology



Charge 5 devices at once



Compact design



World-to-World adapter

### Charge around the world

The Verbatim GaN III Universal Travel Adapter UTA-05 is a compact and versatile solution for travelers. It supports over 180 countries, offering EU, UK, US, Australia, and China plug options. Utilizing advanced GaN III technology, it's more efficient and compact.

This 5-in-1 adapter allows simultaneous charging of five devices through AC and USB ports, including two USB-C with Power Delivery 3.0 (with PPS support), Quick Charge 4+ output, up to 65W each, and USB-A port supports Quick Charge 3.0 output, up to 60W. The other USB-A port has a regular output of up to 5W.

Ideal for international travel, this adapter ensures you gives you 100% peace of mind wherever you may go.

# UTA-05

GaN III Universal Travel Adapter with  
2x USB-C PD 65W & QC 4+ / 2x USB-A

| PN    | Description                                                                                | Bar Code     | EAN128 Code                     | EAN14 Code     |
|-------|--------------------------------------------------------------------------------------------|--------------|---------------------------------|----------------|
| 32120 | Verbatim UTA-05 GaN III Universal Travel Adapter with 2 x USB-C PD 65W & QC 4+ / 2 x USB-A | 023942321200 | (02)00023942321200(37)20(91)489 | 50023942321205 |

## General Information

|                               |                                                                                                |
|-------------------------------|------------------------------------------------------------------------------------------------|
| Input Plug Formats            | Type A / B / C / E / F / G / I / J / L / N                                                     |
| Output Plug Formats           | EU, UK, USA/Japan, AUS/China<br>Type A / B / C / D / E / F / G / H / I / J / K / L / M / N / O |
| Material                      | Fire-proof polycarbonate, Copper (Pouch: Nylon + PVC)                                          |
| Product Dimensions LxWxH (mm) | 78 x 55 x 54                                                                                   |
| Product Weight (grams) approx | 177                                                                                            |
| Colour                        | Black                                                                                          |
| Safety shutter                | Yes, can only be opened with force of more than 75N (7.5Kg) per hole                           |

## Power

|                     |                                                 |
|---------------------|-------------------------------------------------|
| AC Input            | 100-250V, 50-60Hz                               |
| Rating              | 100-250V, 10A Max, 2500W Max                    |
| Total DC Output     | 65.0W                                           |
| Earthed Plug        | No                                              |
| Fuse                | 10A, 250V (spare fuse included)                 |
| Fuse Compliance     | BS1362                                          |
| Charging Technology | PD3.0, QC4+, FCP, SCP, AFC, PPS, BC1-2 and more |

## Single Port Output

|                                          |                                                                               |
|------------------------------------------|-------------------------------------------------------------------------------|
| USB-C1<br>PD 3.0 & QC 4+ (PPS supported) | 3.3-11V=5A, 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 15.0V=3.0A, 20.0V=3.25A 65W Max |
| USB-C2<br>PD 3.0 & QC 4+ (PPS supported) | 3.3-11V=5A, 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 15.0V=3.0A, 20.0V=3.25A 65W Max |
| USB-A1 QC 3.0                            | 4.5V=5.0A, 5.0V=4.5A, 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 20.0V=3.0A 60W Max    |
| USB-A2                                   | 5.0V=1.0A 5.0W Max                                                            |

| Multiport Max Output        | USB-C1 | USB-C2 | USB-A1 | USB-A2 |
|-----------------------------|--------|--------|--------|--------|
| USB-C1+USB-C2               | 20W    | 45W    | -      | -      |
| USB-C1+USB-A1               | 15W    | -      | 15W    | -      |
| USB-C1+USB-A2               | 65W    | -      | -      | 5W     |
| USB-C2+USB-A1               | -      | 45W    | 18W    | -      |
| USB-C2+USB-A2               | -      | 65W    | -      | 5W     |
| USB-C1+USB-C2+USB-A1        | 15W    | 45W    | 15W    | -      |
| USB-C1+USB-C2+USB-A2        | 20W    | 45W    | -      | 5W     |
| USB-C1+USB-A1+USB-A2        | 15W    | -      | 15W    | 5W     |
| USB-C2+USB-A1+USB-A2        | -      | 45W    | 18W    | 5W     |
| USB-C1+USB-C2+USB-A1+USB-A2 | 15W    | 45W    | 15W    | 5W     |

# UTA-05

GaN III Universal Travel Adapter with  
2x USB-C PD 65W & QC 4+ / 2x USB-A

## Other Features

|                               |                                                                                                                                                 |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Indoor use                    | Yes                                                                                                                                             |
| Outdoor use                   | No                                                                                                                                              |
| LED Indicators                | Yes                                                                                                                                             |
| Protective Functions          | Safety shutter for child protection; can only be opened with force of more than 75N (7.5Kg) per hole                                            |
| Compliance                    | EN 55032:2005/A11:2020<br>EN 55035:2017/A11:2020<br>EN IEC61000-3-2: 2019/A1:2021<br>EN 61000-3-3: 2013/A1:2019<br>EN IEC 62638-1:2020+A11:2020 |
| ROHS Directive                | 2011/65/EC                                                                                                                                      |
| Electromagnetic Compatibility | 2014/30/EC                                                                                                                                      |
| General product Safety        | 2001/95/EC                                                                                                                                      |

## Storage and Operating Conditions

|                       |               |
|-----------------------|---------------|
| Storage Temperature   | -20°C to 85°C |
| Operating Temperature | 0°C to 35°C   |
| Operating Humidity    | 25% to 90% RH |

## Logistic Information

|                          |                                             |
|--------------------------|---------------------------------------------|
| Pack Dimensions LxWxH    | 90.6 x 62.7 x 105.6 mm (132 mm with hanger) |
| Pack Weight              | 242 g                                       |
| Pcs per Pack             | 1                                           |
| Outer Cartons Dimensions | 330 x 230 x 200 mm                          |
| Outer Cartons Weight     | 5 340 g                                     |
| Pcs per Outer Carton     | 20                                          |
| Outer Carton per Layer   | 15                                          |
| Layers per Pallet        | 6                                           |
| Pcs per Pallet           | 1 800                                       |



# UTA-05

GaN III Universal Travel Adapter with  
2x USB-C PD 65W & QC 4+ / 2x USB-A

**Verbatim**  
Technology you can trust



Front



Back



Right angled UK plug



Right angled EU plug



Left angled USB



Right angled USB



Packaging flat



Packaging 3D

## Pack Contents:

- GaN III Universal Travel Adapter
- Travel pouch
- Quick Start Guide

## Warranty

- 2 Year Limited Warranty

## Warning

- THIS IS NOT A VOLTAGE CONVERTER
- FOR INDOOR USE ONLY
- NO GROUNDING: THIS PRODUCT IS FOR USE WITH UNEARTHED OR DOUBLE INSULATED APPLIANCES ONLY

For more information, please  
contact your key account manager

Publication date: 03-11-2023  
© 2023 Verbatim. All rights reserved.  
All brand names are registered trademarks of their respective owners.  
Unauthorized use strictly prohibited.  
Specifications are subject to change without prior notice.