Verbatim
Technology you can trust

UTA-05

GaN III Universal Travel Adapter with 2x USB-C PD 65W & QC 4+ / 2x USB-A



- 65W GaN III — GaN III charging technology
- Charge 5 devices at once
- Compact design
- World-to-World adapter

Charge around the world

The Verbatim GaN III Universal Travel Adapter UTA-05 is a compact and versatile solution for travelers. It supports over 180 countries, offering EU, UK, US, Australia, and China plug options. Utilizing advanced GaN III technology, it's more efficient and compact.

This 5-in-1 adapter allows simultaneous charging of five devices through AC and USB ports, including two USB-C with Power Delivery 3.0 (with PPS support), Quick Charge 4+ output, up to 65W each, and USB-A port supports Quick Charge 3.0 output, up to 60W. The other USB-A port has a regular output of up to 5W.

Ideal for international travel, this adapter ensures you gives you 100% peace of mind wherever you may go.

Verbatim
Technology you can trust

UTA-05

GaN III Universal Travel Adapter with 2x USB-C PD 65W & QC 4+ / 2x USB-A

PN	Description	Bar Code	EAN128 Code	EAN14 Code
32120	Verbatim UTA-05 GaN III Universal Travel Adapter with 2 x USB-C PD 65W & QC 4+ / 2 x USB-A	023942321200	(02)00023942321200(37)20(91)489	50023942321205

General Information	
Input Plug Formats	Type A / B / C / E / F / G / I / J / L / N
Output Plug Formats	EU, UK, USA/Japan, AUS/China Type A / B / C / D / E / F / G / H / I / J / K / L / M / N / O
Material	Fire-proof polycarbonate, Copper (Pouch: Nylon + PVC)
Product Dimensions LxWxH (mm)	78 x 55 x 54
Product Weight (grams) approx	177
Colour	Black
Safety shutter	Yes, can only be opened with force of more than 75N (7.5Kg) per hole
Power	
AC Input	100-250V, 50-60Hz
Rating	100-250V, 10A Max, 2500W Max
Total DC Output	65.0W
Earthed Plug	No
Fuse	10A, 250V (spare fuse included)
Fuse Compliance	BS1362
Charging Technology	PD3.0, QC4+, FCP, SCP, AFC, PPS, BC1-2 and more
Single Port Output	
USB-C1 PD 3.0 & QC 4+ (PPS supported)	3.3-11V⎓5A, 5.0V⎓3.0A, 9.0V⎓3.0A, 12.0V⎓3.0A, 15.0V⎓3.0A, 20.0V⎓3.25A 65W Max
USB-C2 PD 3.0 & QC 4+ (PPS supported)	3.3-11V⎓5A, 5.0V⎓3.0A, 9.0V⎓3.0A, 12.0V⎓3.0A, 15.0V⎓3.0A, 20.0V⎓3.25A 65W Max
USB-A1 QC 3.0	4.5V⎓5.0A, 5.0V⎓4.5A, 5.0V⎓3.0A, 9.0V⎓3.0A, 12.0V⎓3.0A, 20.0V⎓3.0A 60W Max
USB-A2	5.0V⎓1.0A 5.0W Max

Multiport Max Output	USB-C1	USB-C2	USB-A1	USB-A2
USB-C1+USB-C2	20W	45W	-	-
USB-C1+USB-A1	15W	-	15W	-
USB-C1+USB-A2	65W	-	-	5W
USB-C2+USB-A1	-	45W	18W	-
USB-C2+USB-A2	-	65W	-	5W
USB-C1+USB-C2+USB-A1	15W	45W	15W	
USB-C1+USB-C2+USB-A2	20W	45W	-	5W
USB-C1+USB-A1+USB-A2	15W	-	15W	5W
USB-C2+USB-A1+USB-A2	-	45W	18W	5W
USB-C1+USB-C2+USB-A1+USB-A2	15W	45W	15W	5W

UTA-05

GaN III Universal Travel Adapter with 2x USB-C PD 65W & QC 4+ / 2x USB-A

Verbatim
Technology you can trust

Other Features	
Indoor use	Yes
Outdoor use	No
LED Indicators	Yes
Protective Functions	Safety shutter for child protection; can only be opened with force of more than 75N (7.5Kg) per hole
Compliance	EN 55032:2005/A11:2020 EN 55035:2017/A11:2020 EN IEC61000-3-2: 2019/A1:2021 EN 61000-3-3: 2013/A1:2019 EN IEC 62638-1:2020+A11:2020
ROHS Directive	2011/65/EC
Electromagnetic Compatibility	2014/30/EC
General product Safety	2001/95/EC

Storage and Operating Conditions	
Storage Temperature	-20°C to 85°C
Operating Temperature	0°C to 35°C
Operating Humidity	25% to 90% RH

Logistic Information	
Pack Dimensions LxWxH	90.6 x 62.7 x 105.6 mm (132 mm with hanger)
Pack Weight	242 g
Pcs per Pack	1
Outer Cartons Dimensions	330 x 230 x 200 mm
Outer Cartons Weight	5 340 g
Pcs per Outer Carton	20
Outer Carton per Layer	15
Layers per Pallet	6
Pcs per Pallet	1 800





www.verbatim.com

UTA-05

GaN III Universal Travel Adapter with 2x USB-C PD 65W & QC 4+ / 2x USB-A



Front


Back


Right angled UK plug


Right angled EU plug



Left angled USB



Right angled USB



Packaging flat


Packaging 3D

Verbatim™
Technology you can trust

Pack Contents:
- GaN III Universal Travel Adapter
- Travel pouch
- Quick Start Guide

Warranty
- 2 Year Limited Warranty

Warning
- THIS IS NOT A VOLTAGE CONVERTER
- FOR INDOOR USE ONLY
- NO GROUNDING: THIS PRODUCT IS FOR USE WITH UNEARTHED OR DOUBLE INSULATED APPLIANCES ONLY

For more information, please contact your key account manager

Publication date: 03-11-2023
© 2023 Verbatim. All rights reserved.
All brand names are registered trademarks of their respective owners.
Unauthorized use strictly prohibited.
Specifications are subject to change without prior notice.