



## POLY Edge B20 IP Phone and PoE-enabled

**Brand :** POLY

**Product code:** 82M83AA

**Product name :** Edge B20 IP Phone and PoE-enabled

- Hear every nuance of your call. Poly HD voice and Poly Acoustic Fence technologies give you business-grade audio quality with reduced background noise.
  - Simplicity right out of the box. No need to guess if you are on mute, speakerphone, or headset <sup>[1]</sup>. These keys light up when selected. Instantly add co-workers to your call with 5-way local audio conferencing.
  - Poly cloud management software makes these phones the smart choice. IT can easily monitor, manage, and maintain devices securely from the cloud with PDMS-SP and Poly Lens software.
- Edge B20 IP Phone and PoE-enabled

**POLY Edge B20 IP Phone and PoE-enabled:**

Call with confidence

Sleek design meets quality audio at an affordable price. Easy-to-use illuminated keys, plug-and-play provisioning, and reliability make it pure value.



| Design                      |                                                  | Ports & interfaces                |             |
|-----------------------------|--------------------------------------------------|-----------------------------------|-------------|
| Product type *              | IP Phone                                         | RJ-9 ports quantity               | 1           |
| Handset type                | Wired handset                                    | <b>Certificates</b>               |             |
| Product colour *            | Black                                            | Sustainability certificates       | ENERGY STAR |
| Wall mountable              | ✓                                                | <b>Power</b>                      |             |
| Mounting                    | Desk/Wall                                        | Power over Ethernet (PoE) *       | ✓           |
| Phone features              |                                                  | Operational conditions            |             |
| Lines quantity *            | 2 lines                                          | Operating temperature (T-T)       | 0 - 40 °C   |
| Caller ID *                 | ✓                                                | Operating relative humidity (H-H) | 5 - 95%     |
| Display                     |                                                  | Storage temperature (T-T)         | -40 - 70 °C |
| Display                     | LCD                                              | Weight & dimensions               |             |
| Display diagonal            | 7.11 cm (2.8")                                   | Package width                     | 176 mm      |
| Touchscreen *               | ✗                                                | Package depth                     | 163 mm      |
| Audio                       |                                                  | Package height                    | 44 mm       |
| Speakerphone *              | ✓                                                | Package weight                    | 900 g       |
| Voice codecs                | G.711alaw, G.711ulaw, G.722, G.729ab, OPUS, iLBC | Packaging content                 |             |
| Network                     |                                                  | Mounting kit                      | ✓           |
| Ethernet LAN *              | ✓                                                | Handset                           | ✓           |
| Ethernet LAN interface type | Gigabit Ethernet                                 | Number of handles included *      | 1 pc(s)     |
| Ethernet LAN data rates     | 10,100,1000 Mbit/s                               | Cables included                   | LAN (RJ-45) |
| Wi-Fi *                     | ✗                                                | AC adapter included               | ✓           |
| Bluetooth *                 | ✗                                                | Stand included                    | ✓           |
| Ports & interfaces          |                                                  | Logistics data                    |             |
| Headset connectivity        | 3.5 mm                                           | Country of origin                 | China       |
| Ethernet LAN (RJ-45) ports  | 2                                                |                                   |             |



0197497341317



197497341317

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-MAY-2024. Prints or copies of Information are only valid on the printed Publication date