


REV.	REVISED DESCRIPTION	DATE	CHECKED
A0	FIRST RELEASE	2018/08/10	







A)Conductor 7/0.12BC
B)Insulation HDPE 0.9mm(White/Green)
C)Conductor 7/0.20BC
D)Insulation PVC 1.1mm(Red/Black)
E)Al Foil
F)Drain wire 7/0.12CCS
G)Braiding: 64/0.12AL
J)Jacket OD:4.5±0.15mm Black

28+24AWG USB Cable Spec.

Remark:
1.100% Open/Short Test
2.Conductive Resistance:2ohms MAX
3.Insulation Resistance:5M ohm MIN.
4.The product is Reach/RoHS compliant.

Item NO.	Length(m)
SB2520	1.8m
SB2530	3.0m
SB2550	5.0m

ITEM	DESCRIPTIONS & SPECIFICATIONS		QTY	REMARK
③	External Mold	Outer Mould 45P PVC, Black	2PCS	
②	Connector	USB A Male, Nickle-Plated	2PCS	
①	Cable	28+24 USB Cable OD:4.5mm 28+24 (7/.012BC+HDPE)*1P + (7/0.20BC +PVC)*2C+7/0.12CCS+64/0.12ALB +OD4.5PVC Black		

TOLERANCES UNLESS OTHERWISE STATED
X. = ± 1
.X = ± 0.2
.XX = ± 0.1

ACT

ERP NO.:		SAMPLE DWG NO:	
DOC No.:		REVISION	A0
CUSTOMER:		UNIT	mm
CUSTOMER P/N:		SCALE	NO
DESCRIPTION	28+24 USB A Male TO A Male	PAGE NO	1/1
		DATE	2018/08/10
APPROVAL	CHECKED	DRAWN	