

EPIC® H-B 16 TG

Housing design H-B. The industry standard.

The robust housing for rectangular connectors with a direct cable entry is suitable for use in lighting and sound systems.

Info

Non-slip ridges for comfortable disconnection of the connector

Protection rating tested according to UL50E



Waterproof



Robust



Mechanical resistance



Industrial machinery and plant engineering



Automation & fältinstallation

Benefits

The standard for housing. Wide choice for various applications

Application range

Plant construction

Event equipment

Plastics industry

Last Update (06.06.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® H-B 16 TG

Product features

Hood, low version
Bolts for double lever
Straight cable entry
Versions with/without collar

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000437 ETIM 5.0 Class-Description: Housing for industrial connectors
Material:	Housing: Powder-coated aluminium alloy, grey Lever: Steel, galvanised Seal: NBR
Protection rating:	IP 65 (latched)
VDE-tested:	Certified production control: VDE reg. no.: B437 UL-tested: UL file number: E75770
Temperature range:	-40°C to +100°C, short-term up to +125°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® H-B 16 TG

Article number	Article description	PG	Collar
H-B housing: Hood (straight cable entry, bolts for double lever)			
10080000	H-B 16 TG 21	21	yes
10090000	H-B 16 TG 29	29	yes
19080000	H-B 16 TG M25	25	
19090000	H-B 16 TG M32	32	

Last Update (06.06.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16