

# 351023 Wireless 1D Laser Barcode Scanner, with Stand

## Product Images



## Short Description

---

- Wireless 1D Laser Barcode Scanner.
- Precise scanning of 1D barcodes.
- Efficiently deciphers linear barcodes for retail and inventory management.
- Wireless Connectivity: Cordless operation using 2.4GHz RF technology for increased mobility.
- Durable Construction: Robust design to withstand daily use and potential drops.
- Protected and water-resistant (IP54).
- Wide Scan Range: Reads barcodes from various distances and angles.
- Multiple Scanning Modes: Options for continuous, single, or presentation mode scanning.
- Plug-and-play functionality for quick setup
- Pairing ability base station support up to 4 scanners connection
- Memory save over 2,000 scans data (@ barcode length < 15 bytes)
- Power charging station included.
- Build in battery 3.7V 1500mAh Li-ion. Working time : around 20hours, Standby: 3 months

## Description

---

The Equip Wireless 1D Laser Barcode Scanner with Stand is a versatile and efficient scanning solution for businesses. This device, designed for various applications, including retail and inventory management, offers the flexibility of wireless operation and the convenience of a stand for hands-free use.

With wireless capabilities, it provides freedom of movement, making it an ideal choice for scanning barcodes on products, shelves, or inventory. The included stand enhances productivity, particularly in busy retail or warehouse settings.

This 1D laser barcode scanner offers quick and precise barcode reading, simplifying data capture and reducing errors. Its wireless connectivity ensures seamless integration with your systems. This scanner streamlines operations, improves inventory accuracy, and enhances customer service, making it a cost-effective solution for businesses. It's a reliable tool for organizations seeking an efficient way to manage 1D barcoded information while maintaining flexibility and convenience.

## Additional Information

|                              |                                                                                                                    |
|------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Color                        | Black                                                                                                              |
| EAN                          | 4015867231692                                                                                                      |
| Model Number                 | 351023                                                                                                             |
| Decoding Type 1D             | Code128、EAN-13、EAN-8、Code39、UPC-A、UPC-E、Codabar、Interleaved 2 of 5、ISBN/ISSN、Code93、Code11、UCC/EAN-128、GS1 Databar |
| Depth of Field               | 0~75mm (13mil EAN13 PCS 90%)                                                                                       |
| Light Source (color)         | Red LED 650nm±10%                                                                                                  |
| Protection                   | IP54                                                                                                               |
| Scan Angle                   | Horizontal: 70°, Vertical : 70°                                                                                    |
| Scan Distance                | 700mm                                                                                                              |
| Scan Speed                   | 200 Scans / per sec                                                                                                |
| Scan Width                   | 5mm~300mm                                                                                                          |
| Trigger Mode                 | Manual, Continuous Scan, Auto-induction Scan                                                                       |
| Connection mode              | 2.4GHz Wireless                                                                                                    |
| Approval and Compliance      | CE, RoHS                                                                                                           |
| Operating humidity           | 5% RH ~ 95% RH                                                                                                     |
| Operating temperature        | -20°C ~ 60°C                                                                                                       |
| Compatible operating systems | WIN XP/7/8/9/10 Android IOS LINUX                                                                                  |
| Storage temperature          | -40°C ~ 85°C                                                                                                       |
| Package Contents             | Barcode Scanner Quick Installation Guide Holder Stand<br>USB-A to C Cable 2.4Ghz USB Receiver                      |
| Cable length                 | 1.8M                                                                                                               |
| Dimensions (W x D x H)       | 72 x 101 x 175 mm                                                                                                  |
| Product weight (kg)          | 0.19                                                                                                               |
| Wireless connection          | Yes                                                                                                                |
| Battery capacity (mAh)       | 1500mAh                                                                                                            |
| Battery capacity (Wh)        | 5.55Wh                                                                                                             |
| Battery type                 | Lithium Ion                                                                                                        |
| Battery voltage              | 3.7v                                                                                                               |
| Material                     | ABS                                                                                                                |

|              |                    |
|--------------|--------------------|
| Power supply | USB DC 5V          |
| Resolution   | $\geq 4\text{mil}$ |

