



Art.-Nr. / *Item No.*	Länge / *Length* (L)
72315	500 ± 20 mm
72316	1000 ± 30 mm
72317	1500 ± 30 mm
72318	2000 ± 30 mm
72319	3000 ± 30 mm

Aderquerschnitt / *Wire cross section*



Anschlussdiagramm / *Wiring diagram*





Premium High-Speed-HDMI™ Kabel mit Ethernet

- offiziell zertifiziert durch das Premium-HDMI™-Kabel-Zertifizierungsprogramm

Anschlüsse:	2x HDMI™-Stecker (Typ A)
Kontakte:	vergoldet
Material:	PE, PVC 45P
AWG:	30
Kontaktwiderstand:	3 Ω max.
Isolationswiderstand:	5 MΩ min.
Max. Auflösung:	4K Ultra HD 2160p (60 Hz)
Max. Datenübertragungsrate:	18 Gbit/s
Unterstützte Farbräume:	Deep Color (36 Bit), x.v.Colour (xvYCC), YCbCr 4:4:4
Unterstützte Standards:	HDR (High Dynamic Range), HDMI™ Ethernet Channel (HEC), 4K 3D, 21:9 Cinemascope, HDCP 2.2, Consumer Electronics Control (CEC), Audio Return Channel (ARC), Audio (1536 kHz)

Premium High Speed HDMI™ cable with Ethernet

- officially certified by the Premium HDMI™ cable certification program

Connectors:	*2x HDMI™ plug (Type A)*
Contacts:	*gold-plated*
Material:	*PE, PVC 45P*
AWG:	*30*
Contact resistance:	*3 Ω max.*
Insulation resistance:	*5 MΩ min.*
Max. resolution:	*4K Ultra HD 2160p (60 Hz)*
Max. data transmission rate:	*18 Gbit/s*
Supported colour spaces:	*Deep Color (36 Bit), x.v.Colour (xvYCC), YCbCr 4:4:4*
Supported standards:	*HDR (High Dynamic Range), HDMI™ Ethernet Channel (HEC), 4K 3D, 21:9 Cinemascope, HDCP 2.2, Consumer Electronics Control (CEC), Audio Return Channel (ARC), Audio (1536 kHz)*

Änderungen			Datum	Name
Datum	Name	gez.:	26.07.2021	rs
		gepr.:	26.07.2021	aw
		Norm:		
		Änderungen vorbehalten / *Subject to change*		

Bezeichnung

HDMI 2.0 Kabel Zert. XXXX
Xm STD sw

Zeichnungs-Nr.:

72315, 72316, 72317, 72318, 72319

Blatt **1/1**

von