

ALTHEA17B 3-Port 67W GaN USB PD Charger with USB-C Charging Cable, USB-C x 2, USB-A x 1, QC 3.0, PPS

Product Images



Short Description

- USB-C 1 output: DC 5.0V/3.0A, 9.0V/3.0A, 12.0V/3.0A, 15.0V/3.0A, 20.0V/3.35A (PD); 3.3-11.0V/4.05A (PPS)
- USB-C 2 output: DC 5.0V/3.0A, 9.0V/2.22A, 12.0V/1.67A (PD); 3.3-11.0V/1.8A (PPS)
- USB-A output: DC 5.0V/3.0A, 9.0V/2.0A, 12.0V/1.5A (QC 3.0)

- USB-C 1 + USB-C 2 + USB-A output: 45.0W (USB-C 1) + 5.0V/3.0A (USB-C 2 + USB-A)
- USB Power Delivery (PD) 3.0 technology with quick charge function
- Complies to Programmable Power Supply (PPS) to enhance charging efficiency and reduce heat
- Protected against overload, short circuiting and overheating
- Includes a 1.5m 3.0A USB-C to USB-C cable

Description

The USB PD charger provides a safe, reliable and convenient secondary power solution for the home or office, as well as a versatile option for when you are travelling. The device is also a perfect replacement for a broken or lost adapter. Automatically detects and charges devices such as MacBook, Nintendo Switch, Samsung etc., at up to 67W speed. This charger is protected against overload, short circuiting and overheating.

Additional Information

Color	Black
EAN	4015867236512
Model Number	ALTHEA17B
Approval and Compliance	CE, ERP, RoHS
Operating humidity	20% RH ~ 80% RH
Operating temperature	0°C ~ 35°C
Storage humidity	10% RH ~ 90% RH
Storage temperature	-20°C ~ 80°C
Package Contents	ALTHEA17B 1.5m 3.0A USB-C to USB-C cable Multilingual quick installation guide
Dimensions (W x D x H)	54 x 54 x 32 mm
Product weight (kg)	0.128
Output Power (watt)	67.0
Power input	AC 100.0-240.0V, 1.5A max, 50-60Hz

