

3m USB 3.2 Type A to C Cable, 5A PD, Anthra Line

No.: 36919

USB Type A Male to C Male

Description

- Professional choice USB 3.2 Gen 2 Type A to C, 5A (100W), cable for commercial and high performance AV and IT installations
- SuperSpeed USB 10Gbps - supports data transfer speeds up to 10Gbps (USB 3.2 Gen 2, USB 3.1 Gen 2, USB 3.1) and Power Delivery
- Robust TPE housing, gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- 2 year warranty

The Anthra Line USB 3.2 Type A to C, 5A, cables from Lindy's Cable Lines concept are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 3.2 cables are premium connections that feature triple shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

USB bandwidths up to 10Gbps are supported for rapid transfer of large data volumes. These cables are E-marked to provide 100W (20V 5A) of power to devices using the most efficient power delivery profiles.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Anthra Line USB 3.2 Type A to C, 5A cables are available in the following lengths: 0.5m, 1m, 1.5m, 2m and 3m.

We have adapted the naming of our USB 3 cables to follow the updated USB specification.
USB 3.0 and USB 3.1 Gen 1 have been renamed to USB 3.2 Gen 1, supporting data transfer up to 5Gbps
USB 3.1 and USB 3.1 Gen 2 are now called USB 3.2 Gen 2, supporting data transfer rates up to 10 Gbps
USB 3.2 Gen 2x2 is a new standard, supporting data transfer rates up to 20 Gbps
USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

Technical details

Connectors

- Connector A: USB 3.2 Type A Male
- Connector B: USB 3.2 Type C Male
- Housing Material: TPE

Shielding in head shell: Copper Foil
Connector Plating: Gold
Pin Construction: Copper
Pin Plating: Gold
Dimensions (approx.) WxDxH:
A:16x47x8.8mm (0.63x1.85x0.35in)
B:13x41x7.75 mm (0.51x1.61x0.31in)

Cable Construction

Length: 3m (9.84ft)
Standard: USB 3.2 Gen 2 (USB 3.1 Gen 2, USB 3.1)
Power Delivery: -
Max. Power: 15W
Colour: Black
Type: Round
Jacket Diameter: 5.2mm (0.2in)
Jacket Material: TPE
Conductor Material: Tinned Copper
Conductor Gauge Power: 22AWG
Conductor Gauge Data: 28AWG/28AWG
Shielding: Tinned Copper 65%

Specifications

Supported Bandwidth: 10Gbps
Maximum Resolution: -
Nominal Attenuation: 0.5Mhz-15Ghz_40dB
Minimum Bend Radius: 26mm (1.02in)
Operating Temperature: 0°C - 40°C (32°F -104°F)
Storage Temperature: -20°C - 60°C (-4°F -140°F)

Miscellaneous

Packaging Type: Polybag
Warranty (Years): 2
Product Compliance: RoHS, REACH, California Proposition 65 & UL

Purchasing Information

No.: 36919
EAN: 4002888369190

This product is also available in other lengths

36910 - 0.5m (1.64ft)
36911 - 1m (3.28ft)
36912 - 1.5m (4.92ft)
36913 - 2m (6.56ft)
36919 - 3m (9.84ft)

© LINDY 2024