ZEUS51E2K 2000VA 2000W Online UPS, IEC

Product Images







Short Description

- Output power factor 1.0
- ECO mode for energy saving
- Wide Input Range (80V-300V)
- Generator compatible
- Provides HID compatible USB connection
- Emergency Power Off (EPO) port
- Easy battery replacement
- THDi≤5%
- Outlet programmable management

Description

The Conceptronic Online UPS is the ultimate solution for reliable battery backup in your home or office. With an output power factor of 1.0, this UPS ensures maximum efficiency and performance. The ECO mode feature helps save energy, making it an environmentally friendly choice. Designed for compatibility with generators, it provides

continuous power even during extended outages.

The Conceptronic Online UPS includes a HID-compatible USB connection for seamless communication with your devices and an Emergency Power Off (EPO) port for added safety during emergencies. The easy battery replacement feature allows for convenient maintenance. Additionally, the outlet programmable management feature enables you to customize power distribution according to your needs.

Simple to install and operate, the Conceptronic Online UPS offers a dependable and efficient way to protect your systems from power surges and failures, ensuring the smooth operation of your critical equipment.

Additional Information

Color	Black
EAN	4015867235454
Model Number	ZEUS51E2K
Protection	UPS Output Cut off Immediately or Input Fuse / Circuit Breaker Protection
Approval and Compliance	CE, RoHS
Operating humidity	20% RH ~ 90% RH
Operating temperature	0°C ~ 40°C
Package Contents	ZEUS51E2K Multilingual quick installation guide Input power cord EU Input power cord UK Rackmount ears (Stands) x2 Flat head screws: M4x8Lx8 Screw hole dust covers x8 Pan head screws:M5x12Lx4 Plastic washers x8 USB cable RS232 cable
Recharge time	4hr
Dimensions (W x D x H)	438 x 430 x 88 mm
Product weight (kg)	17.32
Alarm	Battery Mode, Battery Low, Overload, UPS Fault, Replace Battery, Bypass Mode, Charger Failure /Over Charged, Fan failure, EPO active
Battery capacity (mAh)	9000
Battery capacity (Wh)	108
Battery voltage	DC 12V
Button	Power On/Off
Display	Graphic LCD
Number of ports	8
Output Power (watt)	2000
Power input	AC 220-240V, 10A max, 50/60Hz
Power Output	AC 220-240V
Power rating	2000VA

Types of ports	IEC
UPS Type	Online double conversion
Waveform	Sine wave

