



DATASHEET

RALLY BAR HUDDLE

VIDEO ENABLE HUDDLE AND SMALL ROOMS. ALL-IN-ONE VIDEO CONFERENCING AT THE TOUCH OF A BUTTON.

ALL-IN-ONE VIDEO BAR FOR HUDDLE AND SMALL ROOMS


Designed to deliver video meetings with ease, Rally Bar Huddle is quick to set up in person or remotely, simple to manage, and easy to integrate with your existing video conferencing solutions through CollabOS.

Rally Bar Huddle works with most platforms you use to connect hybrid teams, ensuring an effortless experience from the home to the office, and everywhere in between.

Combine Rally Bar Huddle with Tap IP and Tap Scheduler to make it easy to schedule, join, and participate in video meetings.

EVERYONE IS SEEN AND HEARD CLEARLY

AI video intelligence, advanced sound pickup, noise suppression, and ongoing software improvements provide a clear and natural meeting experience for remote workers.



WORKS WITH LEADING VIDEO PLATFORMS

Rally Bar Huddle works with most platforms you use to connect hybrid teams, ensuring an effortless experience from the home to the office, and everywhere in between.



QUICK TO SET UP, EASY TO MANAGE



Designed to deliver video meetings with ease, Rally Bar Huddle is quick to set up, simple to manage, and easy to integrate with Tap IP through CollabOS. Plus, use the included Multi Mount to mount Rally Bar Huddle one of three ways; on the wall, on the table, or above the display.

Plus, use Rally Bar Huddle as a meeting room appliance, in USB mode connected to a meeting room PC, or connect via laptop.



PC



APPLIANCE



BYOD



DIMENSIONS	SYSTEM REQUIREMENTS	PACKAGE CONTENTS	WARRANTY INFORMATION
Width: 549.6 mm (21.6 in) Height: 78.9 mm (3.1 in) Depth: 76.0 mm (3.0 in) Weight: 3.9 lbs (1.8 kg)	Internet Connection: Wired or wireless USB Mode: Windows® 11, Windows 10, the two most recent versions of macOS Appliance Mode: Room solution software license (not included)	Rally Bar Huddle Multi-Mount Power supply AC power cord HDMI cable USB cable	Standard: 2-year limited hardware warranty included. Extended: Additional one-year and three-year extended warranties available at the time of hardware purchase. Contact your reseller for availability.
TECHNICAL SPECIFICATIONS			
Certifications and Compatibility: For the latest information on certification and compatibility, see prosupport.logi.com/hc/en-us/articles/1500001344641. General Specifications: Built-in Components: 6 DMIC microphone array, digital PTZ camera, 1 full range ported speaker, cable management & retention system, Multi Mount, integrated motorized privacy shutter, Logitech CollabOS platform Enclosure: All-in-one enclosure with field replaceable front cover Device Management: Logitech Sync Displays Supported: 1 (2nd display support is coming soon) Display Resolution: 1080p Network Protocol Support: IPv4, IPv6 Proxy Support: IP based Proxy, FQDN based Proxy, Proxy using PAC file Camera: Digital Pan: ±48° at 4x zoom Digital Tilt: ±32° at 4x zoom Zoom: 4X HD digital zoom Diagonal Field of View: 120° Horizontal Field of View: 113° Vertical Field of View: 80° Resolution: 4k Speakers: Driver: 55 mm with bass reflex enclosure and patented suspension design Sensitivity: 83 dB SPL @1W +/-2dB @ 1 meter Rated Power: 8W THD at 1W, 1kHz: <2% Speaker Sampling Rate: 48KHz Impedance: 4 Ohms Microphones: Frequency Response: 90Hz –16kHz Sensitivity: -36dBFS +/-1 dB @ 1Pa Microphone data rate output: 48 kHz Pickup Range: Up to 23 ft (7m) Beamforming Elements: Six omnidirectional digital MEMS microphones forming five adaptive acoustic broadside beams Audio processing: AEC (Acoustic Echo Cancellation), VAD (Voice Activity Detector) Noise suppression: AI based de-noising algorithm Interfaces: HDMI Out: 1 HDMI In: 1 USB: 1x Type A USB 3.1, 1x Type C USB 3.1 Network: 10/100/1G Ethernet WiFi: 802.11a/b/g/n/ac Bluetooth: Bluetooth® Low Energy Power and Cables: Power supply: Auto-sensing Operating Voltage/Power: 100-240V, 19V, 2.1A Power Supply Dimensions: 4.48 in (114 mm) x 1.85 in (47 mm) x 1.27 in (32.3 mm) DC Cable: 5 ft (1.5 m) AC Cable: 4.9 ft (1 m) HDMI 1.4 Cable: 6.5 ft (2 m) USB A to USB C 3.0 Cable: 7.2 ft (2.2 m) Environmental: Operating Temperature: 0 to 40°C Storage Temperature: -25 to 70°C Humidity: 10 to 90% Security: File Based Encryption: AES-128 Data Encryption: Symmetric Keys, PKI Device Identity: Protected by device attestation Device Access: Authenticated using API Key Protection: Arm TrustZone, RPMP Accessories: Covers: Rally Bar Huddle Front Cover-Cleanable, Off-White Fabric Mounts: Wall Mount for Video Bars, TV Mount for Video Bars Touch Controller: Logitech Tap (coming soon) and Tap IP			
PART NUMBER			
960-001485			