

VI 600-1000 MS

- HID (Human Interface Device) support for USB communication without additional software
- 8 Outlets (4 with battery backup, 4 standard)
- Automatic Voltage Regulator
- USB charging port (2.1A)
- Easily replaceable batteries from compartment
- Wall mountable



PowerWalker VI MS is a line-interactive UPS series with multiple sockets. 4 sockets with battery backup for critical loads and 4 sockets with bypass for non critical loads. The integrated AVR function ensures clean and stable output during power outages or voltage fluctuations. The UPS functions can be monitored and controlled via USB communication, either with a software or without (HID).

The multi socket design makes the VI MS series especially suitable for home and office applications. The UPS can be used on top of a desk or it can be mounted to a wall. Applications include home office, workstations, NAS etc.

Furthermore, the USB charging port (2.1A) offers additional functionality, and the design allows access to the battery compartment via the back panel for easy battery replacement.



MODEL	VI 600 MS	VI 800 MS	VI 1000 MS
Power (VA)	600VA	800VA	1000VA
Power (W)	360W	480W	600W
INPUT			
Voltage	230Vac		
Voltage Range	170-280Vac		
Frequency Range	50/60Hz (Auto)		
OUTPUT			
Voltage Regulation	230Vac ±10 %		
Frequency Range	50/60Hz		
Transfer Time AC to Battery	Typical 6 ms, maximum 10 ms		
Waveform (Bat. Mode)	Simulated Sine Wave		
Protection	Discharge, Overcharge and Overload Protection		
BATTERY			
Type	1x 12V / 7Ah	1x 12V / 9Ah	1x 12V / 9Ah
Recharge Time	6-8h to 90% after complete discharge		
Protection	Battery Discharge, Overcharge and Overload Protection		
CONNECTIONS AND COMMUNICATION			
Output	8x Schuko or 8x French or 8x UK		
Protection Port	RJ11/RJ45 (Ethernet Surge Protection)		
Software	ViewPower		
Communication Ports	1x USB port with HID support		
Charger Ports	1x USB port 5V/2.1A		

