

Blackmagic PYXIS 6K



\$2,995

Blackmagic PYXIS 6K is an advanced digital film camera with an incredibly versatile design that lets you build the perfect camera rig for your production. This new model features a 6048 x 4032 full frame HDR sensor with built in optical low pass filter, dual native ISO, dual CFexpress media slots, all in a customizable body with flexible mounting options and side plates. Blackmagic PYXIS 6K is available in three different models with fixed L-Mount, PL or locking EF lens mounts.

Camera Features

Effective Sensor Size

36mm x 24mm (Full Frame)

Lens Mount

Active L-Mount.

Lens Control

Iris and focus on supported lenses.

Dynamic Range

13 Stops.

Dual Native ISO

400 and 3200

Shooting Resolutions

6048 x 4032 (Open Gate 3:2) up to 36 fps
 4832 x 4032 (Anamorphic 6:5) up to 36 fps
 6048 x 3200 (6K DCI 17:9) up to 48 fps
 6048 x 2520 (6K 2.4:1) up to 60 fps
 4096 x 3072 (Super 35 4:3) up to 50 fps
 4096 x 2160 (4K DCI 17:9) up to 60 fps
 2112 x 1184 (Super 16 16:9) up to 100 fps
 1920 x 1080 (1080 HD 16:9) up to 120 fps

Frame Rates

Maximum sensor frame rate dependent on resolution and codec selected. Project frame rates of 23.98, 24, 25, 29.97, 30, 50, 59.94 and 60 fps supported.

Off-speed frame rates up to 60 fps in 6K 2.4:1 and 4K DCI 17:9, 100 fps in Super 16 16:9 and 120 fps in 1080HD.

Focus

Auto focus available using compatible lenses.

Iris Control

Iris wheel and touchscreen slider for manual iris adjustment on electronically controllable lenses, iris button for instant auto iris settings on compatible lenses.

Screen Dimensions

4" 1920 x 1080.

Screen Brightness

1500 nits

Screen Type

LCD capacitive touchscreen.

Metadata Support

Automatically populated lens data from electronic L-Mount lenses. Automatic recording of camera settings, motion sensor data plus slate data such as project, scene number, take and special notes. A 3D LUT can also be embedded in metadata of Blackmagic RAW files.

Controls

Touchscreen menus on 4 inch screen. 1 x Power Switch, 1 x Record Button, 1 x Stills Button, 1 x Scroll Wheel with push, 1 x ISO Button, 1 x White Balance, 1 x Shutter Button, 3 x software configurable Fn buttons, 1 x Focus Button, 1 x IRIS Button, 1 x High Frame Rate (HFR) Button, 1 x Zoom Button, 1 x Menu Button, 1 x Playback Button, 1 x Next Clip Button, 1 x Previous Clip Button, 1 x Lock Switch.

Timecode Clock

Highly accurate timecode clock. Less than 1 frame drift every 8 hours.

Connections

Total Video Inputs

None

Total Video Outputs

1 x 12G-SDI up to 2160p60

1 x Viewfinder USB-C with power, data, video and locking connector.

Analog Audio Inputs

1 x mini XLR analog audio in, switchable between mic with phantom power support and line level (up to +14dBu).

1 x 3.5mm Stereo Input.

Analog Audio Outputs

1 x 3.5mm headphone jack.

Reference Inputs

Tri-Sync/Black Burst and Timecode.


Computer Interface

USB Type-C for external drive recording,

PTP camera control and software updates.

Ethernet

1 x 1Gb/s RJ-45 connector supporting 10/100/1000 BASE-T.



Audio

Microphone

Integrated stereo microphone.

Built in Speaker

1 x mono speaker.

Media

Media

2 x CFexpress Type B card slot, 1 x USB-C 3.1 Gen 1 expansion port for external media for Blackmagic RAW and H.264 Proxy Recording. Please refer to either the Manual or the Information Note at www.blackmagicdesign.com/support for compatible media.

Media Format

Can format media to ExFAT (Windows/Mac) or HFS+ (Mac) file systems.

Supported Codecs

Codecs

Blackmagic RAW Constant Bitrate 3:1,
Blackmagic RAW Constant Bitrate 5:1,
Blackmagic RAW Constant Bitrate 8:1,
Blackmagic RAW Constant Bitrate 12:1,
Blackmagic RAW Constant Quality Q0,
Blackmagic RAW Constant Quality Q1,
Blackmagic RAW Constant Quality Q3,
Blackmagic RAW Constant Quality Q5,
H.264 Proxy in 1920 x 1080, 8-bit 4:2:0

Control

External Control

Blackmagic Zoom Demand and Blackmagic Focus Demand for controlling your camera and lens from tripod handles.

iPad control, Bluetooth control, USB PTP camera control. External control of some camera settings, focus, iris and zoom with compatible lenses. Camera Control REST API over Ethernet for external control via HTTP when used with REST client applications such as Postman.

Storage Features

Storage Type

2 x CFexpress Type B

1 x high speed USB-C expansion port for external media.

Recording Formats

Blackmagic RAW 3:1, 5:1, 8:1, 12:1, Q0, Q1, Q3 and Q5 at 6048 x 4032, 4832 x 4032, 6048 x 3200, 6048 x 2520, 4096 x 3072, 4096 x 2160, 2112 x 1184 and 1920 x 1080 with film, extended video, video dynamic range or custom 3D LUT embedded in metadata.

Supports recording optional portrait mode metadata for all resolutions in Blackmagic RAW and H.264 Proxies.

Storage Rates

Storage rates based on 30 frames per second.

6048 x 4032 (6K Open Gate 3:2)	4096 x 3072 (Super 35 4:3)
Blackmagic RAW 3:1 - 370 MB/s	Blackmagic RAW 3:1 - 192 MB/s
Blackmagic RAW 5:1 - 223 MB/s	Blackmagic RAW 5:1 - 116 MB/s
Blackmagic RAW 8:1 - 140 MB/s	Blackmagic RAW 8:1 - 73 MB/s
Blackmagic RAW 12:1 - 94 MB/s	Blackmagic RAW 12:1 - 49 MB/s
Blackmagic RAW Q0 - 278 to 555 MB/s	Blackmagic RAW Q0 - 145 to 288 MB/s
Blackmagic RAW Q1 - 186 to 444 MB/s	Blackmagic RAW Q1 - 97 to 231 MB/s
Blackmagic RAW Q3 - 124 to 318 MB/s	Blackmagic RAW Q3 - 65 to 165 MB/s
Blackmagic RAW Q5 - 75 to 186 MB/s	Blackmagic RAW Q5 - 39 to 97 MB/s
4832 x 4032 (Anamorphic 6:5)	4096 x 2160 (4K DCI 17:9)
Blackmagic RAW 3:1 - 297 MB/s	Blackmagic RAW 3:1 - 136 MB/s
Blackmagic RAW 5:1 - 179 MB/s	Blackmagic RAW 5:1 - 82 MB/s
Blackmagic RAW 8:1 - 112 MB/s	Blackmagic RAW 8:1 - 52 MB/s
Blackmagic RAW 12:1 - 75 MB/s	Blackmagic RAW 12:1 - 35 MB/s
Blackmagic RAW Q0 - 223 to 445 MB/s	Blackmagic RAW Q0 - 102 to 203 MB/s
Blackmagic RAW Q1 - 149 to 356 MB/s	Blackmagic RAW Q1 - 69 to 163 MB/s
Blackmagic RAW Q3 - 100 to 255 MB/s	Blackmagic RAW Q3 - 46 to 117 MB/s
Blackmagic RAW Q5 - 60 to 149 MB/s	Blackmagic RAW Q5 - 28 to 69 MB/s
6048 x 3200 (6K DCI 17:9)	2112 x 1184 (Super 16 16:9)
Blackmagic RAW 3:1 - 295 MB/s	Blackmagic RAW 3:1 - 40 MB/s
Blackmagic RAW 5:1 - 177 MB/s	Blackmagic RAW 5:1 - 24 MB/s
Blackmagic RAW 8:1 - 111 MB/s	Blackmagic RAW 8:1 - 16 MB/s
Blackmagic RAW 12:1 - 75 MB/s	Blackmagic RAW 12:1 - 11 MB/s
Blackmagic RAW Q0 - 221 to 441 MB/s	Blackmagic RAW Q0 - 30 to 59 MB/s
Blackmagic RAW Q1 - 148 to 353 MB/s	Blackmagic RAW Q1 - 21 to 48 MB/s
Blackmagic RAW Q3 - 99 to 253 MB/s	Blackmagic RAW Q3 - 14 to 34 MB/s
Blackmagic RAW Q5 - 60 to 148 MB/s	Blackmagic RAW Q5 - 9 to 21 MB/s
6048 x 2520 (6K 2.4:1)	1920 x 1080
Blackmagic RAW 3:1 - 233 MB/s	Blackmagic RAW 3:1 - 33 MB/s
Blackmagic RAW 5:1 - 140 MB/s	Blackmagic RAW 5:1 - 20 MB/s
Blackmagic RAW 8:1 - 88 MB/s	Blackmagic RAW 8:1 - 13 MB/s
Blackmagic RAW 12:1 - 59 MB/s	Blackmagic RAW 12:1 - 9 MB/s
Blackmagic RAW Q0 - 175 to 348 MB/s	Blackmagic RAW Q0 - 25 to 49 MB/s
Blackmagic RAW Q1 - 117 to 279 MB/s	Blackmagic RAW Q1 - 17 to 40 MB/s
Blackmagic RAW Q3 - 78 to 199 MB/s	Blackmagic RAW Q3 - 12 to 29 MB/s
Blackmagic RAW Q5 - 47 to 117 MB/s	Blackmagic RAW Q5 - 8 to 17 MB/s

Constant Quality storage rates quoted are indicative only.

Actual storage rates are entirely dependent on image subject matter.

Software

Software Included

- Blackmagic OS
 - DaVinci Resolve Studio for Mac and Windows including activation key
 - Blackmagic Camera Setup
 - Blackmagic RAW Player
 - Blackmagic RAW QuickLook Plugin
 - Blackmagic RAW SDK
 - Blackmagic RAW Speed Test
-

Operating Systems



Mac 13.0 Ventura,
Mac 14.0 Sonoma or later.



Windows 10 and 11.

Power Requirements

Power Supply

1 x External 12V power supply.

Battery Type

BP-U

External Power Input

1 x 2-pin locking connector.

Power

11-19.5V

Accessories

Optional Accessories

- Blackmagic URSA Cine Handle
- Blackmagic URSA Cine EVF
- Blackmagic PYXIS Rosette Plate

Physical Specifications



Environmental Specifications

Operating Temperature

0°to 40°C (32° to 104°F)

Storage Temperature

-20°to 45°C (-4° to 113°F)

Relative Humidity

0% to 90% non-condensing

What's Included

- Blackmagic PYXIS 6K
 - Lens turret dust cap
 - PYXIS Standard Plate
 - PYXIS SSD Plate
 - 60W power supply with locking connector and international adapters
 - Welcome booklet
 - DaVinci Resolve Studio activation key
-

Warranty

Product Warranty

12 Month Limited Manufacturer's Warranty.

Blackmagic Design Authorized Reseller