


Product Images





Short Description

- 4 x 2 AWG 26/7
- Unshielded
- 500MHz performance Bandwidth
- Transmission: 10Gbit
- Suitable for PoE, PoE+
- Stranded bare copper conductor
- Molded boot with Strain relief
- RoHS compliant
- Low Smoke Zero Halogen (LSZH/LSOH)
- Compliant with ISO/IEC 11801 and EN 50173

Description

The equip® Cat.6A U/UTP Patch Cord is composed of preeminent materials and fully-examined to conform with industrial standards. Offering higher bandwidth and better signal-to-noise margin, the Cat.6A cable is able to deliver ultrahigh and error-free performance in the most demanding network environments, specially for 10G application.

Additional Information

Harmonized System (HS) code	854442
Customs product code (TARIC)	85444210
Angled Plug	No
Flat cable	No
Shielded	No
Shielding	U/UTP
Connector 1	RJ45 male
Connector 2	RJ45 male
Approval and Compliance	RoHS
Package Contents	Cat.6A U/UTP Patch Cable
Cable Length	0.15m
Dimensions (W x D x H)	11 x 15 x 150m
Product weight (kg)	0.01
Color	Black
EAN	4015867237007
Model Number	603151
Category	Cat.6A
Conductor material	Copper
Conductor size (AWG)	26AWG
Jacket material	LSZH

