

OPENS THE
DOOR TO THE
SMART HOME

Door Lock Drive

HmIP-DLD | HmIP-DLD-A | HmIP-DLD-S

No more searching for the key? The intelligent door lock drive by Homematic IP makes it possible! Unlocking, locking and opening of doors is done conveniently and securely via smartphone or remote control. The Homematic IP app keeps an eye on your entrance door at all times.



Also available in anthracite and silver



homematic ^{IP}
Smart living, simply comfortable

CONVENIENT & FLEXIBLE ACCESS CONTROL

It is now possible to easily lock, unlock and even open doors at any time while on the move or from the couch. Simply by Homematic IP app or key ring remote control. Another advantage: Secure locking of the door is also possible by voice control (with Amazon Alexa or Google Assistant).

EASILY DETERMINE WHO MAY ENTER YOUR HOME

Thanks to configurable access authorisations, access to your smart home can be managed individually – no matter for which day of the week or at what time. The front door can only be opened if you want it to. This means, for example, that cleaning staff or care services can enter the house only at certain times using the key ring remote control.

IS THE FRONT DOOR REALLY LOCKED?

Thanks to time-dependent locking, this question becomes unnecessary. At a defined time, the front door is automatically locked (e.g. at night). This not only increases the security in the smart home, but also saves you from having to check the front door when it is not necessary.

If you want to be on the safe side, you can have the front door automatically locked again after each time it is unlocked. Set-points and delay times can be set individually via the app.

HIGHLY SECURE

The door lock drive benefits from the VDE-certified protocol, IT and data security of the Homematic IP system. As it is mounted on the inside of the door, the device is not visible from the outside.

Operation requires connection to one of the following solutions:

- Homematic IP Access Point with free smartphone app and free cloud service
- Third-party solutions of partners

TECHNICAL SPECIFICATIONS


Supply voltage	3x 1.5 V LR6/mignon/AA or 3x 1.2 V HR6/mignon/AA
Battery life	1/2 year (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	56 x 118 x 63 mm
Weight	328 g (including batteries)
Radio frequency band	868.0-868.60 MHz 869.4-869.65 MHz
Typ. open area RF range	200 m

EASY TO RETROFIT

Easily mounted on standard profile cylinders with emergency and danger function – without damaging the door, frame or key. Thanks to battery operation, no wiring is necessary. For mounting, the lock cylinder must protrude 8-15 mm on the inside of the door.



SUITABLE FOR UNIVERSAL USE



ADDITIONAL ADVANTAGES

- ✓ Up to 8 access authorisations with individual time profiles can be created for each door lock drive
- ✓ Manual opening and closing possible at any time via the rotary wheel (emergency function)
- ✓ The door can still be opened from the outside with a standard key
- ✓ Personal PINs to protect against unauthorised operation via app
- ✓ Environmentally friendly operation when using NiMH batteries type HR6

LOGISTICAL DATA

Version	White	Anthracite	Silver
Product reference	154952A0	160555A0	160556A0
EAN code	4047976549528	4047976605552	4047976605569
Short description	HmIP-DLD	HmIP-DLD-A	HmIP-DLD-S
Packing unit		30	
Packing dimensions		184 x 112 x 97 mm	
Weight incl. packaging		529.2 g	

PACKAGE CONTENTS

Homematic IP Door Lock Drive
Mounting plate
Mounting material and batteries
User manual