

# ZEUS52ES1K 1000VA 900W Online Tower UPS, Schuko

## Product Images



## Short Description

- Output Power Factor 0.9
- ECO Mode for Energy-Saving
- Generator Compatible
- Provides HID compatible USB connection
- Emergency Power Off (EPO) Port
- THDi≤5%

## Description

Introducing the Conceptronic Online Tower UPS—the premier power backup solution for your home or office. Featuring an output power factor of 0.9, this UPS delivers superior efficiency and performance. Its ECO Mode enhances energy savings, while compatibility with generators ensures uninterrupted power during extended outages.

The Conceptronic Online Tower UPS comes with HID USB communication for seamless device connectivity and enhanced control and monitoring. For added safety during

emergencies, it includes an Emergency Power Off (EPO) port for swift shutdowns in critical situations.

With its sleek, modern tower design, the Conceptronic Online Tower UPS integrates effortlessly into any environment, providing reliable power backup when you need it most.

## Additional Information

|                              |                                                                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Harmonized System (HS) code  | 8504406090                                                                                                                           |
| Customs product code (TARIC) | 8504406090                                                                                                                           |
| Protection                   | UPS Output Cut off Immediately or Input Fuse / Circuit Breaker Protection                                                            |
| Approval and Compliance      | CE, RoHS                                                                                                                             |
| Operating humidity           | 0% RH ~ 90% RH                                                                                                                       |
| Operating temperature        | 0°C ~ 40°C                                                                                                                           |
| Package Contents             | ZEUS52ES1K Multilingual quick installation guide<br>Input power cord EU USB cable RS232 cable                                        |
| Recharge time                | 4hr                                                                                                                                  |
| Alarm                        | Battery Mode, Battery Low, Overload, UPS Fault, Replace Battery, Bypass Mode, Charger Failure /Over Charged, Fan failure, EPO active |
| Battery capacity (mAh)       | 9000                                                                                                                                 |
| Battery capacity (Wh)        | 108                                                                                                                                  |
| Battery voltage              | DC 12V                                                                                                                               |
| Switches/Buttons             | Power On/Off, Enter, ESC                                                                                                             |
| Display                      | Graphic LCD                                                                                                                          |
| Port Configuration           | Schuko x 3, USB, RS-232                                                                                                              |
| Power input                  | AC 220-240V, 10A max, 50/60Hz                                                                                                        |
| Power Output                 | AC 220-240V                                                                                                                          |
| Power rating                 | 1000VA                                                                                                                               |
| UPS Type                     | Online double conversion                                                                                                             |
| Waveform                     | Sine wave                                                                                                                            |
| Dimensions (W x D x H)       | 140 x 327 x 191 mm                                                                                                                   |
| Product weight (kg)          | 10.1                                                                                                                                 |
| Color                        | Black                                                                                                                                |
| EAN                          | 4015867238172                                                                                                                        |

