


VALUE KVM Extender over Cat. 6/6A, HDMI, 4K@30Hz, max. 40m

Product No.	14.99.3043
Manufacturer	VALUE
Manufacturer No.	14.99.3043
EAN (single piece)	7630049633438



KVM Extension over a Cat. 6/6A/7 network cable of up to 70 meters at a resolution of 1080p@60Hz and up to 40 meters at a resolution of 4K@30Hz - perfect for advertising, monitoring systems, home entertainment, conferences, etc.

- Supports KVM functionality
- Resolution up to 4K@30Hz
- Transmission distance: 1080p@60Hz up to 70m, 4K@30Hz up to 40m, by using Cat. 6 or higher network cables
- Supports HDR10
- Automatically adjusts parameters to match different network cables and achieve the best display performance
- No latency
- Plug & Play
- Supports PoC (Power over Cable) - receiver is supplied via the transmitter
- Transmitter (TX) ports: 1x HDMI, 1x RJ-45, 1x USB A
- Receiver (RX) ports: 1x HDMI, 1x RJ-45, 2x USB A
- Dimensions Transmitter/Receiver (each): 20 x 60 x 75 mm
- Weight Transmitter/Receiver (each): 123 g
- Contents: Transmitter, Receiver, Power Supply DC 5V 2A, USB Cable A-A, User Manual

Technical specifications	
Manufacturer	VALUE

Product group	KVM (IP) extensions
Product type	KVM-Extender, HDMI
Colour	black
Scope of delivery	Transmitter, Receiver, Power Supply DC 5V 2A, USB Cable, User Manual
Inputs	2
Outputs	3
Max. distance	40 m
PC/Switch: monitor connection	HDMI
PC/Switch: mouse/keyboard connection	USB
Remote Console: Monitor connection	HDMI
Remote Console: Mouse/Keyboard connection	USB
Max. distance local-remote unit	40
Max. resolution (nominal)	3840 x 2160 @30Hz (max.)
Colour (Design profile)	black
Material (casing)	metal
Dimensions (HxWxD)	20 x 60 x 75 mm
Power supply unit required	yes
Power supply output	DC 5V 2A
Operating temperature min.	-20 °C
Operating temperature max.	60 °C

Storage temperature min.	-30 °C
Storage temperature max.	70 °C
Height	20 mm
Width	60 mm
Depth	75 mm
Weight	246 g
Height of packaging (single piece)	90 mm
Width of packaging (single piece)	280 mm
Depth of packaging (single piece)	320 mm
Package weight (single piece)	0.5 kg