

Product data sheet

Specifications



Renova Surface Single Socket-Outlet Schuko with screwless terminals black

WDE015976

Main

Range	Renova
Product or component type	Socket-outlet
Device presentation	Complete product
Quantity per set	Set of 10

Complementary

Socket number	1
Device mounting	Surface
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	Schuko
Rated current	16 A
Cover type	Full cover plate
[Ue] rated operational voltage	250 V AC
Colour tint	Black (NCS S 9000-N)
Connections - terminals	Screwless terminals
Clamping connection capacity	1 x 1.5...2 x 2.5 mm² for solid cable(s) 1 x 1.5...2 x 2.5 mm² for solid stranded cable(s)
Material	PC (polycarbonate): cover frame PC 10 % GF: bottom-plate
Fixing mode	By screws: insert By screw: cover frame
Diameter	70.0 mm
Embedding depth	0.0 mm
Projecting depth	43.0 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 NEK 502 SFS 5610 SS 4280834
Product certifications	FIMKO NEMKO SEMKO

	CE
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	62.0 g
Package 1 Height	4.3 cm
Package 1 width	6.9 cm
Package 1 Length	6.9 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	744.0 g
Package 2 Height	9.2 cm
Package 2 width	17.6 cm
Package 2 Length	25.8 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	120
Package 3 Weight	9.738 kg
Package 3 Height	29.8 cm
Package 3 width	39.2 cm
Package 3 Length	58.8 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins