





Model: P4

5G SA/NSA


AX3000 Wi-Fi 6 Router



Easy Setup with Cudy App



[Datasheet](#)



2× SMA Connectors
for Extension Antennas

WPS Button

3× Gigabit Ethernet Ports

SIM Card Slot



Reset Button



5G. Wi-Fi 6. Top-Notch Network.


Lightning-Fast 5G up to 3.4 Gbps Download

The Carrier Aggregation and 4×4 MIMO accelerate internet speed and reduce network latency to provide premium networks for bandwidth/latency-sensitive applications.



Carrier Aggregation

Improves stability drastically



4×4 MIMO

Boosts speeds with multiple streams

High-Capacity Wi-Fi 6

The exceptional Wi-Fi performance enables online gaming and HD video streaming at the same time, while large files can be shared with multiple devices.


2.4 GHz 574 Mbps



5 GHz 2402 Mbps



4X
More
Devices



Always-On Internet with WAN Failover

Set the WAN/LAN port to WAN and connect to internet via broadband, then back up your network with the 5G connection to have a more reliable connection.

VPN for Secure Remote Access

ZeroTier/WireGuard/OpenVPN/IPSec/ L2TP/ PPTP are available for boundless VPN applications. Server and client are both supported.



Plug in a SIM Card to Enjoy Network Everywhere





Highlights

A 5G WiFi 6 router employing the 3GPP Release 16 standard, with a max 3.4 Gbps download speed. It features dual Qualcomm chipsets, one SIM slot, and a high-capacity AX3000 WiFi 6.

- 5G Rel. 16 with Max 3.4 Gbps DL
- UL/DL 4CA, 4×4 MIMO
- 4-Stream Dual-Band Wi-Fi 6
- 2402 Mbps + 574 Mbps Wi-Fi
- 3× Gigabit Ethernet Ports
- 1× Nano SIM Slot
- Cudy Mesh, VPN Server and Client
- Cudy App, Cloud Control

Package Content

- P4
- Power Adapter
- Ethernet Cable
- Installation Guide

Hardware Specs

CPU	Chipset	IPQ5018
	CPU Details	1.0 GHz Dual-core, ARM Cortex-A53
Memory /Storage	Flash/ROM	128 MB (1 Gbit) NAND
	DDR/RAM	512 MB (4 Gbit) DDR3L
Cellular	Cellular Standards	5G Rel. 16
		DL 4G Cat. 19 / UL 4G Cat. 18
	Cellular Antennas	6× Internal, 2× SMA Connectors for Customized Antennas
	Detachable Cellular Antennas Connector	SMA Female
	SIM Options	1× Nano SIM Slot, eSIM (optional)
	Available Versions	EU, US
EU Version Cellular	Suitable Region	Europe, Middle East, Africa, Asia-Pacific (Exc. JP, CN), Brazil
	Max DL Speed	3.4 Gbps (NSA), 2.4 Gbps (SA)
	Max UL Speed	550 Mbps (NSA), 900 Mbps (SA)
	Advanced	DL/UL 4CA, DL 4×4, UL 2×2 MIMO
	Cellular Bands	5G Sub 6 GHz: n1/3/5/7/8/20/28/38/40/41/71/75/76/77/78
		LTE-FDD: B1/3/5/7/8/20/28/32/71
		LTE-TDD: B38/40/41/42/43/71
		WCDMA: B1/5/8



Hardware Specs

Wireless	5 GHz Wi-Fi Speed	2402 Mbps
	2.4 GHz Wi-Fi Speed	574 Mbps
	5 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
	2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
	Wi-Fi Antennas	Internal
	Beamforming	True
	FEM or PA/LNA	5 GHz: 2× External
		2.4 GHz: 2× External
	Range Performance	Max: 170 m (558 ft)
Indoor WiFi range varies depending on the layout and wall materials. See Wall		
Performance spec for placement suggestions.		
Wall Performance	One wooden walls with thickness < 10 cm (4")	
	One concrete wall with thickness < 20 cm (7")	
Interfaces	Physical Buttons	WPS Button
		Reset Button
	Gigabit RJ45 Ports	3
	Ethernet Notes	One port supports WAN/LAN configuration, and the rest are LAN ports

Interfaces	LED	Power	
		Internet	
		Wi-Fi	
		Cellular	
Power	Power Input	DC Jack	
	Power Methods	DC	
	DC	12V 2.5A	
	Power Adapter	Input: 100 ~ 240 V, 50/60 Hz AC Output: 12V 2.5A DC	
Reliability	ESD Contact Protection	4kV	
	ESD Air Protection	8kV	
	Environment	Operating Temperature: 0 °C ~ 40 °C (32 °F ~104 °F)	
		Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F)	
		Operating Humidity: 10% ~ 90% non-condensing	
		Storage Humidity: 5% ~ 90% non-condensing	
		Certifications	
		FCC, CE	
		Mechanical	Dimension
Installation	Desktop		



Software Specs

Wireless	Wi-Fi Standards	Wi-Fi 6
	Max Wi-Fi Modulation	1024-QAM
	Wi-Fi Efficiency	OFDMA
		MU-MIMO
		BSS Color
	Max Capacity	256
	Recommended Client Upper Limit	100
	Max Wi-Fi Channel Width	160 MHz
	Wi-Fi Security	WPA/WPA2/WPA3
	Guest Network	2.4 GHz, 5 GHz
General	WPS	True
	Operation Modes	Cellular Router
		Wi-Fi Router
		WISP
	Mesh	Cudy Mesh Main
	Mesh Backhaul	Wireless Backhaul
		Wired Backhaul
	Cellular APN	Band Select (Band Lock)
		Cellular Mode Select
		Data Roaming
		APN Profile
		Manual APN Profile
		MBN
		MTU Value

General	Cellular Mode	5G NSA Only
		5G SA Only
		4G Only
		3G Only
		Auto
	WAN Mode	DHCP
		Static IP
		PPPOE
		L2TP
		PPTP
Network	Internet Failover Sequence	WAN
		WISP
		Cellular
		Per-User Rate Limiting
		Address Reservation
	QoS	DHCP Client List
		Server
		IP Versions
		IPv6 Protocols
		Relay
		Dynamic (SLAAC/DHCPv6)
		Staic (Fixed IP)
		Passthrough
		464XLAT
		MAP-E
	DS-Lite	



Software Specs

Network	IPTV/VLAN	Bridge
		Tag VLAN
	TTL Customization	Extend
		Spoof
		Custom
	IGMP	IGMP Proxy
		IGMP Snooping
	Forwarding	Port Forwarding
		Port Triggering
		UPnP
		DMZ
	Firewall	SPI Firewall
		DoS Protection
		Block PING
	Application Layer Gateway	IPSec Passthrough
		L2TP Passthrough
		PPTP Passthrough
		FTP Passthrough
		TFTP Passthrough
		H323 Passthrough
		SIP Passthrough
		RTSP Passthrough

Utilities	VPN Server	WireGuard
		OpenVPN
		IPsec
		Zerotier
		PPTP
	VPN Client	L2TP
		WireGuard
		OpenVPN
		IPsec
		Zerotier
	DNS Options	PPTP
		L2TP
		DNS over TLS
		Manual DNS
		Rebind Protection
	DNS over TLS Providers	Override Clients' DNS
		Cloudflare
		Google
		Quad9
		Custom
	Wake on LAN	True
	Online Detection	True



Software Specs

System	LED Control	True
	Local Control Method	Config Web Page App Control
Remote Control Method	Config Page via HTTPS	
	App Control	TR069/TR098/TR111/TR181
Firmware Upgrade	Local Update	
	App (Over the Air)	
	Online Update	
Reliability	Timed Reboot	
	Backup and Restore	
Diagnostic Tools	Diagnosis	
	Ping	
	Traceroute	
	NSLookup	
	System Log	
Languages	• English • Bengali • Catalan • Czech	
	• German • Greek • Spanish • French	
	• Hebrew • Italian • Croatian • Hungarian	
	• Khmer • Korean • Dutch • Japanese	
	• Russian • Slovak • Swedish • Romanian	
	• Turkish • Vietnamese • Thai • Ukrainian	
	• Polish • Norwegian • Portuguese	
	• Simplified Chinese • Traditional Chinese	

Management	All Devices Management	Wi-Fi Time Schedule
		MAC Filter
		IP/MAC Binding
	Per-Devices Management	Intenent On/Off
		VPN On/Off
		Online Time Schedule
		Device Rename
	Content Management	Domain Filter
Dashboard	Panel	IP Filter
		Internet Status
		Mesh Status
		Devices Management
		Cellular Status
		SMS Send and Receive
		WAN Status
		LAN Status
		WISP Status
		Wi-Fi Status
		VPN Status
		DHCP Server Status
		System Version
	Charts	Mesh Topology
		Cellular Speed
		Internet Speed
		WISP Speed
		Wi-Fi Speed