

SBG 4910

Metal-cutting band saw with swivelling saw frame

Order no. 390518

GTIN 4030293163195



- + Especially in fire hazardous surroundings the SBG for spark free cutting of metal
- + Cutting without a stand: with 90° straight cut, round and square section, max. 80 mm, rectangular section max. 100 x 80 mm, freehand use 150 x 80 mm
- + Recommended belt speeds: Step I: solid steel, stainless steel, aluminium; Step II: steel, stainless steel, aluminium tubes
- + 2 belt speeds: for sawing solid and hollow sections
- + With stand, easy release for freehand use
- + Continuous tool-free adjustment of the cutting angle from 0° - 45°
- + 3-point ball-bearing bandsaw blade guide for optimum blade control
- + With bracket locking device: for mobile applications and easy transport
- + Work without cooling fluids
- + Safety switch: prevents uncontrolled reactivation following power interruptions



Technical data

Power consumption	850 W
Power output	445 W
Voltage	230 V
Frequency	50/60 Hz
Saw blade length	1335 mm
Saw blade width	13 mm
Saw belt thickness	0.65 mm
Angle adjustment	45°
Cutting length 90°	100 mm
Cutting width 90°	80 mm
Cutting length 45°	68 mm
Cutting width 45°	55 mm
Cable length	4.0 m
Dimensions WxLxH	640 x 310 x 390 mm
Saw frame weight	7.9 kg
Weight	18 kg
Saw blade speed	60/80 m/min

Standard equipment

- 1 Parallel stop (385247)
- 1 Bimetal saw blade