

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration.
- Standard 1 year warranty.



Part #: EP0G90A0

Model Number: VC0ABE2A20B4DXX

Category: Basic

Subcategory: Standard

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 59in / 1500mm, Vertical

Product Summary:

rPDU - Basic Standard, 32A, 230V, 7.3kW, Vertical, (20) Manual Lock IEC C13, (4) Manual Lock IEC C19, 3m power cord with 2P+E (IP44), Black Powder Coat

Plug Form:



1P+N + E

Receptacle:



Manual Lock IEC C13
(Quantity: 20)



Manual Lock IEC C19
(Quantity: 4)

Chassis Color



Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	230V
Current	32A
VA per Input (Load Capacity)	7.3kW
Frequency	50/60Hz
Over Current Protection	(2) 16A Single Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	4mm ² H07RN-F
Power Cable Length	10ft / 3m
Input Type	IEC60309 2P + E, 32A, 250V, Splash proof IP44
Receptacle/Socket Type #1	Manual Lock IEC C13
- Quantity	20
- Quantity per Breaker	10
- Manual Lock Color	Black
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	Manual Lock IEC C19
- Quantity	4
- Quantity per Breaker	2
- Manual Lock Color	Black
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45°C/113F
Heavy Steel - Powder Coat Finish	Black
Configuration	0U, Vertical
Toolless mounting HW – Center to Center	1248mm(vertical mounting bracket included)
Product Warranty	Standard 1 year warranty



Product Specification and Options

System Features

Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	FCC Marked
Certification/Agency Approvals	Complies with IEC 62368-1
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS
Chassis Dimensions (LxWxD)	1500mm x 65.5mm x 45mm
Shipped Weight	4.5kg