ITX A80 Black



ITX A80

The Mini-ITX case A80 by Inter-Tech - modern, stylish and strikingly practical. Completely made of aluminum, it also offers a perfect, thermal relief through various ventilation openings. Its simple design language also makes it look timelessly elegant.

Systems based on Mini-ITX can be designed very energy-saving, so that the standard, external 60W power supply is usually sufficient to run a powerful ITX computer. However, the internal Mini-ITX PSU board is able to handle input voltages of up to 120W.

- ✓Robust full aluminum case
- ✓2x USB 3.0
- ✓including 60W power supply
- ✓high quality feet, chrome plated

Errors excepted. No warranty for the correctness of the information Stand: 14.04.2020

ITX A80 Black

Specifications

Motherboard	ITX
Drive bays	3.5" internal: 1/0* 2.5" internal: 0/2*
Front connectors	USB 3.0: 2 Microphone: - Speaker: -
Case openings	WLAN antenna: 2 COM ports: 3
Cooling system	HDD tray: 2x 40x40x10mm or 50x50x10mm or 60x60x10mm (laterally, optional)
Power input	For 12V plugs with dimensions of 5.5x2.5x10.7mm
Maximum CPU cooler height	40mm[1]/30mm[2]
Maximum graphics card length	-
Packing units	Shipping unit: 1 Piece Packing unit: 6 Pieces
Warranty	24 Months
Article number	88881302
EAN-Code	4260455643399
Scope of delivery	External 60W Power Supply, 12V/5A Mini-ITX PSU max. 120W, 90° Power cord Cable ties Screw set
Features	External 60W power supply Mini-ITX PSU supports 12V power supplies up to 120W Preparation for VESA mount 75x75mm Stands

* the values may differ for certain combinations
[1] without drives, [2] with drives

Dimensions and Weight

	Cage	Case	Package
Height	80mm	88mm	265mm
Width	200mm	200mm	150mm
Depth	200mm	200mm	240mm

Weight (net): 1.07kg
Weight (gross): 1.79kg

DC/DC board:

Connectors	Quantity	Max. Length
Mainboard 20Pin	1x	-
P4 12V 4Pin	1x	60cm
IDE 4Pin	1x	20cm
S-ATA	1x	35cm

DC Output	Output Voltage (V)	Max. Output Current (A)
+3.30 V	+3.30	5.0
+5.00 V	+5.00	5.0
+5.00 VSB	+5.00	2.0
+12.00 V	+12.00	5.0
-12.00 V	-12.00	0.1

Certification: CE

Errors excepted. No warranty for the correctness of the information Stand: 14.04.2020