

MPN: 0070-24143-L-4K

43" 24/7 4K UHD surveillance monitor.

3x HDMI 2.0, 1x DP, Speaker 2x3W

- Screen Size: 43 inches
- Active Display Area: 941.184mm (W) × 529.146mm (H)
- Display Mode: 16:9
- LED Type: TFT-LED
- Resolution: 3840 × 2160
- Display Color: 1.073 billion
- Pixel Pitch: 0.294mm (H) × 0.294mm (V)
- Brightness: 350 nits
- Contrast Ratio: 1000:1
- Viewing Angle: 178° (H) / 178° (V)
- Response Time: 5ms



Backlight: LED

Input & Output: 3 x HDMI 2.0; 1 x DP, Speaker: 2x3W (Stereo)

VideoColor System: PAL/NTSC/SECAM/OSD

Control: Auto adjust, Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase, Color, Language

3D Comb Filter: Yes

Video Noise Reduction: Yes

Power & Mounting: Power Supply: AC 100V~240V, 50/60Hz

Working Temperature: -30 to +85°C Power Consumption: 40W

Menu Languages: English (other languages supported) Mounting Options:

Stand mount,

VESA mount

MTBF: 50,000 hours

Included Accessories:

Screws

Cable holder

Quick start guide

- 24/7 display
- Security monitor
- Desktop monitor

Specifications

Design	Detachable stand	Yes
	Housing material	Plastic
	Market positioning	Industrial
	Product colour	Black
Display	Aspect ratio	16:9
	Contrast ratio (typical)	1000:1
	Display brightness (typical)	110 cd/m ²
	Display diagonal	43 "
	Display number of colours	1.073 billion colours

Display	Display resolution	3840 x 2160 pixels
	Display technology	LCD, LED
	HD type	4K Ultra HD
	Native aspect ratio	16:9
	Pixel pitch	0.2451(H)×0.2451(V) mm
	Response time	5 ms
	Viewable size, horizontal	94.1 cm
	Viewable size, vertical	52.9 cm
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	On Screen Display (OSD) languages	English
	Panel mounting interface	200 x 100 mm
	VESA mounting	Yes
Multimedia	Built-in speaker(s)	Yes
Operational conditions	Operating temperature (T-T)	-30 - +85 °C
Other features	Active display area (W x H)	941.184mm(W)×529.146mm(H) mm
	Analog signal format system	PAL, NTSC, SECAM
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 200 x 200
	Dimensions (WxDxH)	958 x 82 x 564 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	Stand mount, VESA mount 200 x 100 mm
	Noise filter	Yes
	Package dimensions (WxDxH)	1085 x 152 x 638 mm
	Picture enhancement	DNle digital image processing
	Power cord included	Yes
	Speakers	2 x 3W Stereo
	USB ports quantity	1
	Weight	7000 g
Packaging content	Quick start guide	Yes
Performance	Operating hours (hours/days)	24/7
Ports & interfaces	AC (power) in	Yes
	DisplayPorts quantity	1
	HDMI ports quantity	3
	HDMI version	2.0
Power	AC input frequency	50/60 Hz
	AC input voltage	100-240 V

Power	Power consumption (average)	40 W
	Socket connector type	C13
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)

Other images

