

# Alcatel-Lucent Enterprise M7s Pro DeskPhone

The M7s Pro DeskPhone offers a rich SIP communications experience with intuitive navigation and conversation comfort.

This elegant DeskPhone provides super wideband audio in hands-free mode with echo cancelling and full-duplex call performance. The 3.5-inch color screen, makes it quick and easy to connect.

The user experience is enhanced with a 4-way navigation key, 8 line keys, 4 soft keys and a user-friendly interface.

The M7s Pro DeskPhone includes USB-A and USB-C ports making it more than a phone. It is possible to connect to a PC as an external loud speaker to take advantage of the super wideband speaker phone or plug external devices such as Expansion Module (EM200), USB headset, USB key. With the built-in Bluetooth 5.2 and the built-in dual band 2.4G/5G Wi-Fi, the M7s Pro supports wireless deployment.

The M7s Pro DeskPhone includes an adjustable foot stand and comes with customizable faceplates to promote brand awareness.

The standard SIP protocol provides the rich telephony features supported by the major open SIP servers in the market.

The M7s Pro DeskPhone supports both external power and power over Ethernet (PoE, Class 2).

The phone is compatible with ALE Easy Deployment Server (EDS) and Easy Device Management (EDM), providing easy large-scale configuration and deployment.



| Features                                           | Benefits                                                                                                                                                                                                |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Wireless connection                                | Built-in Bluetooth 5.2 allowing easy connectivity to Bluetooth headsets, mobile phones and other devices. Built-in dual band Wi-Fi (2.4G/5G) offering faster speed and improved anti-jamming capability |
| Super wideband audio quality                       | Super wideband audio for speaker phone and wideband audio for the handset                                                                                                                               |
| 3.5-inch color screen and 4-way navigation button  | Easily navigate and connect with colleagues or customers                                                                                                                                                |
| Elegant phone with adjustable foot stand           | Perfect for small desks, hotel rooms and hospital bedsides                                                                                                                                              |
| Customized faceplate                               | Display your organization's logo and create brand awareness                                                                                                                                             |
| Rich telephony features with standard SIP protocol | Benefit from business features such as call management and conference, provided by your preferred cloud PBX provider                                                                                    |
| Effortless deployment                              | Compatible with ALE Easy Deployment Server (EDS) and Easy Device Management (EDM). Saving on manpower with easy large-scale configuration and deployment                                                |

## Datasheet

Alcatel-Lucent Enterprise M7s Pro DeskPhone

## Technical Specifications

### Physical Characteristics

- Height: 183mm (7.2 inches)
- Width: 207mm (8.15 inches)
- Depth: 35mm (1.4 inches)
- Weight: 825g (1.82 lbs)  
(with handset and stand)
- Color: Gray
- Adjustable stand: 40° & 55°
- Wall mountable  
(with an optional accessory)

### Display

- 3.5-inch, 320x240 color display

### Keys

- 8 programmable line keys with LED
- 4 menu keys
- 4-way navigation keys and OK key
- Cancel key
- Volume control keys (+ and -)
- Hands-free, mute and message keys
- Call hold, call transfer and redial key
- Standard dial pad

### Telephony Features

- 8 SIP accounts
- Call forward, call waiting, call transfer, call hold/resume, redial
- Mute/unmute, voicemail, DND, auto answer
- Local 6-party conference
- Call Log (1000 entries)
- Contacts (1000 entries)

### Audio Characteristics

- G.722, OPUS, iLBC
- G.711 (A-law and Mu-law), G.726, G.729AB
- Voice Activity Detection (VAD), Comfort Noise Generation (CNG), Acoustic Echo Cancellation (AEC), Noise Suppression
- DTMF: In-Band, RFC2833, SIP INFO
- Hearing Aid Compatible (HAC)

### Power

- Power over Ethernet (IEEE 802.3af), Class 2
- Power consumption idle/active: 2.2W/3.4W
- Power adapter: 5V/2A DC output (optional)

### Connectivity

- RJ-45 LAN: 10/100/1000M Ethernet
- RJ-45 PC through 10/100/1000M Ethernet switch
- RJ-9 handset connector
- USB-A and USB-C connectors

### Network, Security and others protocols

- SIP V2: RFC 2474, 2833, 3261, 3263, 3264, 3265, 3550, 4566, 5359, 6086
- Static IP and DHCP
- IPv4/IPv6
- IEEE 802.1AB/LLDP-MED
- IEEE 802.3az
- QoS: 802.1p/Q tagging (VLAN), Layer 3 TOS, DSCP
- TFTP/HTTP/HTTPS/TR069
- OpenVPN, 802.1x, OpenSSL 3.x
- Authentication: Basic or digest
- Denial of service (DoS) attack protection: Flooding
- Transport: TLS 1.2 and SRTP/AES-256
- Shipped with (X509v3) certificate installed

### Configuration

- Web-based management
- ALE Easy Device Management (EDM)
- ALE Easy Deployment Server (EDS)

### Languages

- Multi-language support (menu): Arabic, Chinese (simplified), Chinese (traditional), Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hungarian, Icelandic, Italian, Japanese, Korean, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Russian, Slovak, Slovenian, Spanish, Swedish, Thai, Turkish

### Regulatory Standards

#### Safety

- IEC 62368-1: 2023
- EN 62368-1: 2014 +A11: 2017
- CSA C22.2 No. 62368-1-19 and ANSI/UL 62368-1-2019

#### EMC

- EN 55032: 2015+A11:2020
- EN 55035: 2017+A11:2020
- EN 61000-3-2 / IEC 61000-3-2
- EN 61000-3-3 / IEC 61000-3-3
- FCC 47 CFR Part 15 Subpart B
- ICES-003 Issue 7 Canada
- ETSI EN 301 489-1
- ETSI EN 301 489-17

#### Radio

- ETSI EN 300 328
- ETSI EN 301 893
- ETSI EN 300 440
- AS/NZS 4268

- FCC 47 CFR Part 15 C
- FCC 47 CFR Part 15 E
- RSS-Gen issue 5 + RSS-247 issue 2

### Telecommunications Standards

- TIA/EIA 810-B, TIA 920.130-A-1, AS/CA S004

### Eco design

- ErP 2009/125/EC, ErP (EU) 2023/826, WEEE 2012/19/EU
- ROHS 2011/65/EU, CHINA ROHS 2: GBT 26572-2011
- REACH: European regulation: N° 1907/2006
- Proposition 65
- Packaging: EU Directive 94/62/EC

### Hearing Aid Compatibility

- FCC 47 CFR Part 68, CS-03, AS/ACIF S040

### Environmental Conditions

- Operating temperature: -5°C to +45°C
- Relative humidity: 5% to 95%
- Storage/transportation temperature: -25°C/+70°C
- IP Class: IP52

### Ordering Information

- 3MK37020AA M7s Pro DeskPhone

### Accessories

- 3MK27007AA EM200 Expansion Module
- 3MK27008AA Wall Mounting Kit
- 3MK08005US External Power Adapter (US)
- 3MK08005EU External Power Adapter (EU)
- 3MK08005RW External Power Adapter (AU/UK)
- Catalogue for supported headsets

### Packaging

- M7s Pro DeskPhone
- Wired HD wideband handset and cable
- Phone stand
- 1.5m network cable (cat5e)
- Safety sheet
- Quick User Guide

