


Patch panel KS 24x

for 24 modules with Keystone fitting



Patch panel KS 24x, shielded

Blank covers, black and white

DESCRIPTION

Shielded 19"/1U patch panel for up to 24 modules with Keystone fitting.
Snap-in modules can be easily fitted into the patch panel.
Unused ports can be covered with blank covers.
For the modules PS-GG45 7_A Datwyler recommends the patch panel MGK 24x.

Front panel made of flame retardant compound, UL94V-0 rated, in combination with stainless steel and a cable strain relief.
Front in grey, similar to RAL 7035, or in black, similar to RAL 9005.
Strain relief with tie wrap. Delivery without modules.

APPLICATION

Suitable for the following Datwyler modules:

- RJ45 module KS-T Plus 1/8 Cat. 6_A shielded
- RJ45 module KS-TS 1/8 Cat. 6/E_A shielded
- RJ45 module KS-T 1/8 Cat. 6/E_A shielded
- RJ45 module KU-T 1/8 Cat. 6 / Cat. 5e unshielded
- RJ45 module MS-C6_A 1/8 Cat. 6_A 180°-K shielded

DIMENSIONS

Width	482 mm (19")
Depth	160 mm (including cable strain relief)
Height	44 mm (1U)

VERSIONS

Article Number	Product	Colour (similar to)	PU
418019	Patch panel KS 24x, 19"/1U , for 24x RJ45 Keystone modules, FTP (delivery without modules)	black, RAL 9005	1 pc.
418020	Patch panel KS 24x, 19"/1U , for 24x RJ45 Keystone modules, FTP (delivery without modules)	light grey, RAL 7035	1 pc.
418010	Blank cover for Keystone openings	white	10 pcs.
418011	Blank cover for Keystone openings	black	10 pcs.