



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G GAMING OC
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060
Núcleos	3840 Units
Memória	8GB GDDR7
Recommended PSU	550 W
Barramento Padrão	PCI Express® Gen 5 x16 pin(uses x8)
Interface de Memória	128-bit
Velocidade Clock Central (MHz)	Extreme Performance: 2640 MHz (MSI Center) Boost: 2625 MHz
Velocid. Clock Memória (MHz)	28 Gbps
Máximo de Monitores	4
Tecnologia G-SYNC™	Y
Saídas	DisplayPort x 3 (v2.1b) HDMI™ x 1 (Supports 4K@480Hz HDR, 8K@120Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1b)
Suporte HDCP	Y
Consumo de energia (W)	155 W
Resolução máx. Digital	7680 x 4320
Conectores de energia	8-pin x 1
Suporte Versão DirectX	12 Ultimate
Suporte Versão OpenGL	4.6
Dimensões(mm)	248 x 135 x 41 mm
Peso	649 g / 966 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 4

Upgraded fans, airflow control, and thermal design deliver superior cooling and quieter operation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.



Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.