Polaroid Flip
Instant Camera + Color Film Bundle (8 Photos)



Technical Specifications

Product	Polaroid Flip Instant Camera + Color Film Bundle (8 photos)		
Color	**PRD**	**EAN**	**GTIN**
Black	006574	9120134283139	19120134283136
White	006571	9120134283092	19120134283099
Launch Date	TBD		
RRP	$214.99, €224.99, £204.99		
HS or HTS Code	9006409000 (US) 9006400000 (EU)		
Country of Origin	China (CN)		
Packaging Contents	Polaroid Flip Camera Single Pack Color Film for i-Type Neck Strap Quick Start Guide Safety & Compliance Leaflet		
Product Box			
Product Box Weight			
Shipper			
Shipper Weight			
Units per Shipper	6		
Product Dimensions	163.5 x 117.2 x 89.7 mm (lid closed) 163.5 x 117.2 x 121.6 mm (lid open)		
Product Weight	648 grams 22.86 ounces		
Compatible With	i-Type Film 600 Film		
App Enabled	App Enabled Fully control your camera remotely For iOS & Android		
Battery	Lithium-Ion Polymer Soft-Pack Battery. User-serviceable		
Battery Report	Available		

Outer Shell	ABS, PC, PMMA, Mylar, Stainless Steel			
Shutter System	Fastest shutter speed 1/200, exposure time range is 1/200~30s., and Bulb mode (up to 99hrs.)			
Aperture	Maximum f8.5 practical aperture, available apertures: f8.5 - f66.6 (depending on selected zone)			
Lens	Two-lens structure with 4 zones. Auto-switching hyperfocal optical system.			
Field of View	Horizontal: 39.4º Vertical: 40.8º			
Focal Length	**Close-up Lens 1**	**Near Field Lens 2**	**Mid Field Lens 3**	**Far Field Lens 4**
	94.17 mm	97.75 mm	101.4 mm	106.99 mm
Zone range	0.4 m - 0.77 m	0.77 m – 1.03 m	1.03 m - 1.68 m	1.68 m - Infinity
Best focus	.65 m	.85 m	1.2 m	2.5 m
Ranging system	Ultrasonic sensor (0.4 m – 4 m)			
Light meter	40.8° vertical, 39.4° horizontal. Center-weighted single-zone metering (80% coverage of optical FOV)			
Flash System	Vacuum discharge tube strobe range 4.5m @f8 / 14.76' @f8			
Device Interface Ports	USB Type-C charging input x1			
Display	LED display for modes, film count, battery level.			
Other	Bluetooth Viewfinder scene analysis LED warning Tripod mount Built in lens filter snap/click mount			

Distributed by Polaroid International B.V. 1013 AP, Amsterdam, The Netherlands.
POLAROID, the Color Spectrum, and the Classic Border Logo are protected trademarks of Polaroid. Please note that the product is under development. The images in this document are therefore of indicative nature. Please contact your Polaroid sales representative to acquire approved press materials.