

i-tec USB-C/USB-A Cable HUB 4 port (2x USB-C, 2x USB-A)



PRODUCT DESCRIPTION

This HUB provides four USB ports (2× USB-A and 2× USB-A), allowing you to connect your external keyboard and mouse, transfer data or movies from a USB flash drive at speeds up to 5 Gbps, or charge your mobile devices.

No drivers are needed — simply connect the HUB using the USB-C/A cable and start using it right away. Built-in overcurrent protection safeguards your computer in the event of a peripheral short circuit. The interface is also backward compatible with USB 2.0.

Thanks to its compact size and lightweight design, you can easily carry it with you wherever you go.

PRODUCT FEATURES

- 1x integrated USB-A/USB-C cable for connection to the device (10 cm)
- 2x USB-C 3.2 Gen 1 (5Gbps) on a flexible USB cable
- 2x USB-A 3.2 Gen 1 (5Gbps), on a flexible USB cable
- LED indication
- OS: Windows 10/11, macOS, Android, ChromeOS, iPadOS and Linux
- Product dimensions: 250 x 45 x 10 mm
- Product weight: 60 g

Hardware requirements:

- Device with a free USB-A, USB-C, USB4 or Thunderbolt™ 3/4/5 port

Operating System:

- Windows 10/11, macOS, Android, ChromeOS, iPadOS and Linux

SPECIFICATION

PART NUMBER		PRODUCT DESCRIPTION & EAN	
CACBLHUB2A2C		i-tec USB-C/USB-A Cable HUB 4 port (2x USB-C, 2x USB-A) EAN: 8595611707391	
Hardware			
Bus type		USB-C, USB-3.0, Thunderbolt-3, Thunderbolt-4, Thunderbolt-5, USB4	
System Requirements			
Operating system		Windows 10/11 macOS X Android Linux Chrome OS R51 or laterWindows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically.	
Other features			
Product Dimensions		250 x 45 x 10 mm	
Product Weight		60 g	
Support			
Warranty period		2 years	
Technical support		Lifetime	
Package contents			
• Product • Manual			

For further information regarding setup or for answers to FAQ's, please visit our website [i-tec.pro](https://www.i-tec.pro).
Specifications are subject to change without notice.

Updated 02/07/2025 14:02:15