



USB 3.2 Gen 2 Type C Hub & Gigabit Ethernet

No.: 43422

3 Port USB Type A & Type C Hub & Gigabit Ethernet Connection for USB Type C computers

Description

Connects a USB 3.2 Type C computer to a Gigabit Ethernet network
Provides two USB 3.2/3.1 Gen 2 Type A ports and one Type C port
USB 3.2/3.1 Gen 2 SuperSpeed data transfer rates up to 10Gbps
Supports 10/100/1000BASE-T, full and half duplex mode
2 year warranty

The Lindy USB 3.2 Gen 2 Hub & Gigabit Ethernet Converter allows users to conveniently connect a laptop, ultrabook or tablet to a Gigabit Ethernet network via a Type C USB port and also provides two additional USB Type A and one USB Type C device ports. As part of the USB 3.2 Gen 2 specification, 10Gbps bandwidth provides lightning fast data transfers between host and mass storage devices. This hub is also backwards compatible with USB 3.2 / 3.1 Gen 1 / USB 3.0 and USB 2.0.

This converter is ideal for ultrabooks or tablets which do not feature wired network connectivity and may only offer a limited number of USB ports. It features USB Type A and Type C interfaces for connecting a wide range of devices.

With its small size and lightweight design this USB 3.2 Hub & Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

Interface: USB Type C to RJ45 & 2x USB Type A & 1x USB Type C

Interface Standard: USB 3.2 / 3.1 Gen 2, Gigabit LAN

Supported Bandwidth: 10Gbps (USB), 10/100/1000Mbps (LAN)

Chipset: RTL8153 (LAN), GL3590 (Hub)

Compatibility: USB Type C/Thunderbolt equipped computers

Power Delivery: -

Special Features: Supports Wake on LAN (WoL), MAC Address Pass-through

Connectors

Inputs: 1 x USB Type C (Male)

Outputs: 1 x RJ45 (Female), 2 x USB Type A (Female), 1x USB Type C (Female)

Power: Bus-powered

Physical Properties

Dimensions WxDxH: 95x26.4x10.95mm (3.74x1.03x0.43in)

(Fixed) Cable Length: 150mm (5.9in)

Housing Material: Aluminium, Plastic (side parts)

Net Weight: 0.034kg (0.075lb)

Operating Temperature: -25°C - 40°C (77°F -104°F)

Storage Temperature: -25°C - 85°C (-13°F - 185°F)

Humidity: 60 - 95% RH (non-condensing)

Power Requirements: -

Colour: Grey

Miscellaneous

Packaging Type: Polybag

Packaging Dimensions: 174x20x194mm (6.85x0.79x7.64in)

Gross Weight: 0.05kg (0.11lb)

Warranty (Years): 2

Product Compliance: CE, FCC, RoHS, REACH, CP65

Package Contents

USB 3.2 Gen 2 Hub & Gigabit Ethernet Converter

Purchasing Information

No.: 43422

EAN: 4002888434225