

65W GaN Charger

DCP-651

Key Features

- Ensure your devices stay charged while you're on the go with a reliable and efficient charging block
- The block's charging capability includes one USB Type-C port that delivers up to 65W of charging power
- GaN technology facilitates powerful, efficient, and safe charging with comprehensive safety protection
- A compact and convenient multi-port charging block designed to power a variety of devices while minimizing heat buildup
- The USB connectors support a wide range of power outputs, with various maximum capacities
- Designed with advanced protection features: overcurrent, overvoltage, overtemperature, overcharge, and short circuit protection
- USB PD 3.0 and QC 4.0 for fast charging
- Interchangeable power plugs for AU, EU, UK, and US to ensure smooth charging experience when you travel



User Benefits



Supercharged Productivity

GaN technology enables efficient and reliable charging for up to 3 devices simultaneously, ensuring you stay productive and connected wherever you are



Fast Charging

Power your personal devices and gadgets with fast charging capabilities, thanks to standardized charging technologies



Ultra-compact & Portable

With its sleek, rounded edge design, you can easily toss it into your bag without worrying about scratching other items



Power Efficiency with Safety Protection

GaN technology and multifold protection enhance safety and energy efficiency, reducing electricity costs and extending product lifespan



Universal Support

The interchangeable power plugs make it ideal for travel and remote work, capable of charging devices ranging from laptops to phones and tablets



Best On-the-Go Partner

Satisfy your portable charging needs by charging smart and portable accessories safely and efficiently – all at the same time

Technical Specifications

General	
Power Input	100AC-240 V AC (MIN: 90 V, MAX: 264 V) Rated frequency: 50/60Hz Rated Input Current: Max 1.5A@100-240 V input & Full load
Output Interfaces	- When only one charging port is used - USB Type-C1 or C2 - Output: 5.0V@3.0A, 9.0V@3.0A, 12.0V@3.0A, 15.0V@3.0A, 20.0V@3.25A MAX 65W - Output protocol: Power Delivery 3.0 (PD 3.0) and Quick Charge 4.0 (QC 4.0) - USB Type-A - Output: 4.5V@5.0A, 5.0V@4.5A, 5.0V@3A MAX 22.5W - Output protocol: Quick Charge 3.0 (QC 3.0) - When more than one charging port is used - USB Type-C1 & C2: 45.0W & 20.0W - USB Type-C1 & USB Type-A: 45.0W & 18.0W - USB Type-C2 & USB Type-A: Total 15.0W - Maximum Total Output: 65 
Protection	- Overcurrent protection - Overvoltage protection - Overcharge protection - Overtemperature protection - Short circuit protection
Physical	
Dimensions	44.4 x 29.4 x 63.1 mm (1.75 x 1.16 x 2.48 in)
Power Input	MAX 1.5A@100-240 V
Weight	240 g (8.47 oz)
Operating Temperature	0 to 40 °C (32 to 104 °F)
Storage Temperature	-20 to 80 °C (-4 to 176 °F)
Operating Humidity	10% to 100% non-condensing
Storage Humidity	30% to 100% non-condensing
Certifications	CE, FCC
Package Contents	
DCP-651	65W GaN Charger Interchangeable AC Plug (US,UK,EU and AU) Quick Installation Guide Warranty Card