

## Assortments heat shrink tubing

### Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1
- Flame retardant and self-extinguishing
- General purpose
- High flexibility

### Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

### Content assortment 1: 127 pcs H-2(Z) heat shrink tubing (mixed colors)

| Type / Size     | Length in mm | Quantity |
|-----------------|--------------|----------|
| H-2(Z) 1,6/0,8  | 35,0         | 30       |
| H-2(Z) 2,4/1,2  | 35,0         | 25       |
| H-2(Z) 3,2/1,6  | 35,0         | 20       |
| H-2(Z) 4,8/2,4  | 35,0         | 20       |
| H-2(Z) 6,4/3,2  | 70,0         | 16       |
| H-2(Z) 9,5/4,8  | 70,0         | 8        |
| H-2(Z) 12,7/6,4 | 80,0         | 8        |



### Content assortment 2: 127 pcs H-2(Z) heat shrink tubing (black)

| Type / Size     | Length in mm | Quantity |
|-----------------|--------------|----------|
| H-2(Z) 1,6/0,8  | 35,0         | 30       |
| H-2(Z) 2,4/1,2  | 35,0         | 25       |
| H-2(Z) 3,2/1,6  | 35,0         | 20       |
| H-2(Z) 4,8/2,4  | 35,0         | 20       |
| H-2(Z) 6,4/3,2  | 70,0         | 16       |
| H-2(Z) 9,5/4,8  | 70,0         | 8        |
| H-2(Z) 12,7/6,4 | 80,0         | 8        |



### Content assortment 3: 465 pcs H-2(Z) heat shrink tubing (black)

| Type / Size      | Length in mm | Quantity |
|------------------|--------------|----------|
| H-2(Z) 2,4/1,2   | 35,0         | 120      |
| H-2(Z) 3,2/1,6   | 35,0         | 100      |
| H-2(Z) 4,8/2,4   | 35,0         | 80       |
| H-2(Z) 6,4/3,2   | 35,0         | 60       |
| H-2(Z) 9,5/4,8   | 70,0         | 65       |
| H-2(Z) 12,7/6,4  | 70,0         | 15       |
| H-2(Z) 16,0/8,0  | 100,0        | 15       |
| H-2(Z) 19,0/9,5  | 70,0         | 5        |
| H-2(Z) 25,4/12,7 | 70,0         | 5        |

