



KitchenAid Go Cordless System

Cordless Hand Blenders

5KHBRV00BM* - 5KHBRV71BM



- **Removable 17.78 cm blending arm with a 4-point stainless steel blade design**
To efficiently blend ingredients for smoothies, milk shakes, soups, and so much more
- **4-point stainless steel blade design**
Ensures ingredients are easily turned into perfect purées and delicious recipes
- **Ergonomically designed variable speed trigger switch**
Gives greater flexibility and control over the recipe
Allows single-handed operation
- **KitchenAid Go cordless system hand blender**
The power to make, the power to move
Design efficiently blends ingredients for smoothies, milk shakes, soups, and so much more
Make without the hassle of a cord
In- and outdoor usage
- **Rechargeable 12V Lithium Ion battery***
Delivers optimal runtime and performance
Provides up to 30 minutes of continuous runtime**
Eliminates the constraints of a cord
Powers all KitchenAid Go cordless system appliances for cord-free, powerful making
Versatile ecosystem
- **U.S. patented removable pan guard**
To help protect your cookware
- **700 ml BPA-free blending jar and lid**
Great for individual blending jobs or to serve in
- **Complete the KitchenAid Go cordless collection*** including Hand Blenders, Hand Mixer, Food Chopper, Personal Blender, Coffee Grinder and Kitchen Hand Vacuum**
The freedom to make wherever, whatever, and however
One removable battery powers all appliances for easy swapping and maximum versatility, for meal making made easy, for endless possibilities, for maximum versatility



MATTE BLACK

* Battery not included in the model 5KHBRV00BM. Battery sold separately.

**Maximum initial battery voltage (measured without a workload) is 12 volts.

Nominal voltage is 10.8. Actual run time will vary based on recipe and/or attachments used. Battery life impacted by factors such as battery age and use.

*** Each sold separately.

KitchenAid Go Cordless System

Cordless Hand Blenders

5KHBRV00BM - 5KHBRV71BM

TECHNICAL DATA

Motor	DC (Direct current)		
Voltage	12 V		
Number of speeds	2 distinct speeds (variable speed trigger switches)		
Blades speed (min - max)	max. 13500 RPM		
Material of motor body	Plastic		
Product dimensions	H × W × D	37.8 × 7 × 7.9 cm	
Packaging dimensions	5KHBRV00BM	H × W × D	25.7 × 12.2 × 21.1 cm
	5KHBRV71BM	H × W × D	29.8 × 12.2 × 21.1 cm
Master pack dimensions	5KHBRV00BM	H × W × D	26.7 × 21.9 × 25.4 cm
	5KHBRV71BM	H × W × D	30.8 × 21.9 × 25.4 cm
Net weight	5KHBRV00BM	0.8 kg	
	5KHBRV71BM	1.01 kg	
Gross weight	5KHBRV00BM	1.42 kg	
	5KHBRV71BM	1.68 kg	
Master pack gross weight	5KHBRV00BM	3.06 kg	
	5KHBRV71BM	3.6 kg	
Master pack	2 units		
Country of origin	China (Designed in the USA)		
Blender arm of 17.78 cm (Not dishwasher-safe)	Yes		
4-point stainless steel blade design	Yes		
Removable pan guard (dishwasher-safe top rack)	Yes		
Capacity BPA-free blending jar & lid (dishwasher-safe top rack)	700 ml		
Whisk (dishwasher-safe top rack)	No		
Chopper attachment	No		
Storage bag	No		

One interchangeable battery included in model 5KHBRV71BM*/**

Rechargeable Lithium Ion battery	Battery cell type: LR1865LA
Full charge time battery	3 hours
Battery indicator light (LED)	Yes
Power cord type USB-C	Yes
Power adapter	Yes
Charging cord (black) length	91.44 cm
Running time with full battery	30 minutes***
Input USB adapter	100-240 V~, 50-60 Hz, 0.5 A
USB output	5 VDC, 2 A
Nominal voltage external battery	10.8 VDC
Maximum voltage external battery	12 VDC
Average battery lifespan	7 years based on 400 charge cycles

REFERENCES	COLOURS	EAN	EAN MASTER PACK (2 UNITS)
5KHBRV00BM	MATTE BLACK	5413184002848	5413184123932
5KHBRV71BM	MATTE BLACK	5413184002855	5413184123956

* Also available as an optional accessory.
** Not included in the model 5KHBRV00BM. Battery model 5KRB12 can be purchased as an optional accessory.
*** Maximum initial battery voltage (measured without a workload) is 12 volts. Nominal voltage is 10.8. Actual running time will vary based on recipe and/or attachments used. Battery life impacted by factors such as battery age and use.

KitchenAid Go Cordless System

Cordless Hand Blenders

5KHBRV00BM - 5KHBRV71BM

STANDARD ACCESSORIES



700 ml BPA-free graduated hand blender jar with lid
Reduce the need to use multiple measuring cups or bowls.
Easily prepare, serve and store food in a single container.
Dishwasher-safe (top rack only).



Pan guard
Use this pan guard to avoid damage to cookware while using the cordless hand blender.
Dishwasher-safe (top rack only).



Removable blending arm 17.78 cm
To mix, blend, purée, crush, froth, whip and chop all ingredients with ease in bowls, pots or pitchers.
Not dishwasher-safe. Wash in hot, soapy water.



Rechargeable 12V Lithium Ion battery and USB-C cable*//*** 5KRB12**
Easy to charge. Lithium-Ion batteries charge faster, last longer, and have a higher power density for more battery life in a lighter package.
Full Charge: The battery will be fully charged in around 3 hours and when all LEDs are solid.
Does not include a USB adapter.



4-point stainless steel blade
Dishwasher-safe (top rack only).

OPTIONAL ACCESSORIES



Charging dock with fixed cable 5KRBC12
The charging dock has a 91.44 cm length cable. Includes a USB-A to USB-C charging cable.
The KitchenAid Go charging dock is designed for the home to provide a clutter-free space to charge the battery and allows to easily swap in a new battery**** if it runs out.
It plugs into a USB port for convenient charging.

TECHNICAL DATA OPTIONAL ACCESSORIES

		5KRB12 Removable 12V battery	5KRBC12 Docking station
Product dimensions	H × W × D	2.8 × 7 × 7.9 cm	2.475 × 7 × 7.9 cm
Packaging dimensions	H × W × D	10.2 × 6.1 × 10.1 cm	13.6 × 5.5 × 11.7 cm
Master pack dimensions	H × W × D	21.3 × 20.3 × 21.5 cm	14.4 × 23.4 × 36.4 cm
Net weight		0.24 kg	0.08 kg
Gross weight		0.4 kg	0.16 kg
Master pack gross weight		4.94 kg	2.26 kg
Master pack		12 units	12 units

REFERENCES	DESCRIPTION	EAN	EAN MASTER PACK (2 UNITS)
5KRB12	REMOVABLE 12V BATTERY	5413184002947	5413184903053
5KRBC12	DOCKING STATION	5413184002954	5413184903060

* Also available as an optional accessory.
** Not included in the model 5KHBRV00BM. Battery model 5KRB12 can be purchased as an optional accessory.
*** Maximum initial battery voltage (measured without a workload) is 12 volts. Nominal voltage is 10.8. Actual run time will vary based on recipe and/or attachments used. Battery life impacted by factors such as battery age and use.
**** Extra battery sold separately.