



## 1m USB 3.2 Type C Cable, 2 x 90° Right Angle, 10Gbps

No.: 32023

USB Type C Male to Male

### Description

- Entry level USB 3.2 Type C cable for home and small office applications
- Both USB Type C plugs are angled at 90°
- Supports data rates of up to 10Gbps
- Robust PVC housing with nickel-plated contacts
- 10 year warranty

LINDY USB 3.2 Type C cables feature double shielded construction with copper conductors for premium performance and corrosion resistance. Nickel connectors and gold plated contacts maintain signal integrity and reliability.

USB cables with angled plugs protect the USB ports of your devices by reducing pressure and preventing cable breakage, making them ideal for confined spaces and hard-to-reach ports.

Data transfer speeds up to 10Gbps are supported for the quick and effortless transfer of large data volumes.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

USB 3.2 Type C, 2 x 90° Right Angle cables are available in the following lengths: 0.5m, 1m, 1.5m.

### Technical details

#### Connectors

- Connector A: USB 3.2 Type C Male 90° Right Angle
- Connector B: USB 3.2 Type C Male 90° Right Angle
- Housing Material: PVC
- Shielding in head shell: -
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions [approx.] WxDxH: 11.1x25.8x24.2mm [0.44x1.02x0.95in]

#### Cable Construction

- Length: 1m [3.28ft]
- Standard: USB 3.2 Gen 2 [USB 3.1 Gen 2, USB 3.1]
- Power Delivery: PD 2.0

Max. Power: 60W  
Colour: Black  
Type: Round  
Jacket Diameter: 5mm (0.2in)  
Jacket Material: PVC  
Conductor Material: Copper  
Conductor Gauge Power: 22 AWG  
Conductor Gauge Data: 28 AWG  
Shielding: Aluminium Foil 110%

#### **Specifications**

Supported Bandwidth: 10Gbps  
Nominal Attenuation: 0.5Mhz- 400Mhz < 5.8db  
Minimum Bend Radius: 50mm (1.97in)  
Operating Temperature: 0°C - 40°C (32°F - 104°F)  
Storage Temperature: 0°C - 70°C (32°F - 158°F)

#### **Miscellaneous**

Packaging Type: Polybag  
Warranty (Years): 10  
Product Compliance: RoHS, REACH, California Proposition 65

#### **Purchasing Information**

No.: 32023  
EAN: 4002888320238

#### **This product is also available in other lengths**

32022 - 0.5m (1.64ft)  
32023 - 1m (3.28ft)  
32024 - 1.5m (4.92ft)