

# Product data sheet

Specifications



## APC NetShelter Rack PDU Advanced Gen 2, Metered, 3Phase, 43.5kW 400V 63A or 34.6kW 415V 60A, 560P6, 42 Outlet

APDU11450ME

### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### Main

|                           |              |
|---------------------------|--------------|
| Color                     | Black        |
| Product or Component Type | PDU          |
| PDU Type                  | Metered      |
| Cord length               | 9.8 ft (3 m) |

### Complementary

|                             |                                 |
|-----------------------------|---------------------------------|
| Input Voltage               | 415 V 3 phase                   |
| Height                      | 71.9 in (1826 mm)               |
| Width                       | 2.2 in (56 mm)                  |
| Output Voltage              | 240 V                           |
| Depth                       | 3.0 in (75 mm)                  |
| Product Weight              | 25.8 lb(US) (11.7 kg)           |
| Mounting Location           | Side                            |
| Mounting preference         | No preference                   |
| Input Plug Type             | IEC 60309 60 A 3P+N+PE          |
| Mounting Mode               | Rack-mounted                    |
| Rack units                  | 0U                              |
| Mounting position           | Vertical                        |
| Communication Port Protocol | 1000BASE-T<br>10/100BASE-T      |
| Line Rated Current          | 48 A                            |
| Acceptable Input Voltage    | 200...240 V<br>346...415 V      |
| Input current limits        | 60 A                            |
| Load Capacity               | 34600 VA                        |
| Input Frequency             | 50/60 Hz                        |
| Outlet type and quantity    | 21 C13/C15/C19/C21<br>21C13/C15 |

### Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |                                                             |
|---------------------------------------|-------------------------------------------------------------|
| Standards                             | UL 62368-1<br>CSA C22.2 No 62368-1<br>FCC part 15 Subpart B |
| IP Degree of Protection               | IP44                                                        |
| Ambient air temperature for operation | 23...140 °F (-5...60 °C)                                    |
| Relative Humidity                     | 5...95 %                                                    |
| Operating altitude                    | 0...10000 ft                                                |
| Ambient Air Temperature for Storage   | -13...149 °F (-25...65 °C)                                  |
| Storage Relative Humidity             | 5...95 %                                                    |
| Storage altitude                      | 0...50000 ft (0.0000000000...15240.0000000000 m)            |

## Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304752783 |
|------|--------------|

## Packing Units

|                              |                     |
|------------------------------|---------------------|
| Unit Type of Package 1       | PCE                 |
| Number of Units in Package 1 | 1                   |
| Package 1 Height             | 83.07 in (211 cm)   |
| Package 1 Width              | 5.20 in (13.2 cm)   |
| Package 1 Length             | 10.31 in (26.2 cm)  |
| Package 1 Weight             | 37.5 lb(US) (17 kg) |

## Contractual warranty

|          |                           |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

Use Better

|                                                                                                                   |                                      |
|-------------------------------------------------------------------------------------------------------------------|--------------------------------------|
|  <b>Materials and Substances</b> |                                      |
| Packaging made with recycled cardboard                                                                            | No                                   |
| Packaging without single use plastic                                                                              | No                                   |
| <a href="#">EU RoHS Directive</a>                                                                                 | Compliant with Exemptions            |
| SCIP Number                                                                                                       | 31346aed-552c-4a16-81d9-e683a383b6da |
| REACH Regulation                                                                                                  | <a href="#">REACH Declaration</a>    |

Use Again

|                                                                                                                   |    |
|-------------------------------------------------------------------------------------------------------------------|----|
|  <b>Repack and remanufacture</b> |    |
| Take-back                                                                                                         | No |

Image of product / Alternate images

Alternative

---



